

Datasheet RTKSA-002.410

Articlenumber: KA000200

Universal capillary thermostat, 30...110...°C, hysteresis -10...-15K, TB, internal setting, external resetting



| | |
|-------------------------------------|--|
| Ambient temperature, upper value | 80 °C |
| Bearing temperature, lower value | -30 °C |
| Bearing temperature, upper value | 80 °C |
| Capillary length | 2 m |
| Colour | Anthr. grey (RAL7016), frontp. transp. |
| Contact interlocking | Yes |
| Control range, lower value | 30 °C |
| Control range, upper value | 110 °C |
| Cooling control function | Yes |
| Depth | 62,9 mm |
| Device version | Surface-mounted unit |
| Diameter sensor element | 6 mm |
| Electric connection | Push-in terminal |
| Electronic control | No |
| External reset | Yes |
| External setting | No |
| Function type (systems engineering) | TB |
| Heating control function | Yes |
| Height | 146,8 mm |
| Internal setting | Yes |

| | |
|---------------------------------------|--|
| Length of sensor | 72 mm |
| Max. sensor temperature | 126 °C |
| Maximum air humidity (non-condensing) | 95 % r.H |
| Maximum switching current | O: 16 (2,5) A; S: 2 (0,4) A, 0,25 ADC |
| Maximum switching voltage | 230 V AC 50 / 60 Hz, 230 V DC |
| Minimum switching current | At 24 V (AC/DC) min. 100 mA |
| Minimum switching voltage | 24 V AC / 50 Hz, 24 V DC |
| Mounting / attachment | In imm. sleeve, prot. coil, on tube, etc |
| Number of control ranges | 1 |
| Number of outputs | 2 |
| Operating voltage | None |
| Operation | Internal setpoint adjuster |
| Output signal | Switching |
| Potential free switching contact | Yes |
| Protection class | I |
| Safety and EMC | In accordance with DIN EN 60730 |
| Scale | Degree Celsius |
| Sensor element | Capillary tube |
| Sensor material | Cu |
| Switching contact | Two-way contact |
| Switching difference | Manual reset after -10 K ... -15 K |
| Switching difference, can be adjusted | No |
| Switching element | Microswitch |
| Type of protection | IP54 |
| Width | 53 mm |
| With explosion protection | No |

