

rotork®

Keeping the World Flowing
for Future Generations

Schischek Product Range

Compact electric actuators, sensors
and control systems



SCHISCHEK
A ROTORK® Brand

Compact electric actuators,
sensors and control systems
designed for use in hazardous
environments and safe areas.



Rotork is a market-leading global provider of mission-critical flow control and instrumentation solutions for the industrial actuation and flow control markets. These include oil and gas, water and wastewater, power, chemical, process and industrial applications.

Customers rely on us for innovative, high quality and dependable solutions for managing the flow of liquids, gases and powders. We help customers around the world to improve efficiency, reduce emissions, minimise their environmental impact and assure safety.

Our reliability record is second to none. Our products are designed with safety and performance at their core and are put through vigorous testing and certified to international standards. Our products are certified for use in the world's most dangerous and hazardous areas.

Partnering with us provides the following:

- Assured safety and reliability
- Industry leading accuracy and efficiency
- Proven technology that works with all network control systems
- Product range with solutions to suit every application
- Assistance with plant planning, development and maintenance through our local support services
- We have innovative research and development centers throughout the world

Contents

Rotork Group	03	Valve Automation	54
Content Overview	04	Certification	56
Introduction	05	Information About Electrical Explosion Protection	58
Industrial Markets	06	Labelling of Explosionproof Equipment	59
Rotork Service	07	Where and When do I Have to Take	
Which Components Have to be Explosionproof?	08	Explosionproof into Consideration?	60
Product Series	10	Zones • Explosion Groups • Temperature Classes	61
Product Codes/Definitions	50	Ex Applications	62
Installation	52	Damper Actuation Focused	66

Content Overview

Installation Areas

Product series

Page

Gas	Dust	Gas	Dust	Gas	Dust	
0	20	1	21	2	22	SA*
Quarter-turn actuators 90°						
ExMax	size S/M	5...	150 Nm	with/without spring-return	12	
RedMax	size S/M	5...	150 Nm	with/without spring-return	14	
InMax	size S/M	5...	150 Nm	with/without spring-return	16	
Linear valve actuators with spring-return with 7,5/10/15/20/30/42mmstroke (fixed)						
LIN...+ExMax..	size S/M	500...	3.000 N	with spring-return	20	
LIN...+RedMax..	size S/M	500...	3.000 N	with spring-return	20	
LIN...+InMax..	size S/M	500...	3.000 N	with spring-return	20	
Valve actuators with 5...60mm stroke						
ExRun	size S	500...	10.000 N	without spring-return	22	
RedRun	size S	500...	10.000 N	without spring-return	22	
InRun	size S	500...	10.000 N	without spring-return	22	
Special options for actuators						
Overview	special options for actuators					
ExPolar/ExArctic	heating system for actuators use in Ex areas down to -50/-60 °C					
InPolar/InArctic	heating system for actuators use in safe area down to -50/-60 °C					
Controller for volume flow (VAV) and pressure regulation						
ExReg-V	volume flow and pressure controller	0...	1.000 Pa			
InReg-V	volume flow and pressure controller	0...	1.000 Pa			
Analog sensors for measuring of volume flow, temperature, humidity, pressure/differential pressure						
Overview	analogue sensors					
ExCos-P	differential pressure, VAV sensors	± 100...	7.500 Pa			
RedCos-P	differential pressure, VAV sensors	± 100...	7.500 Pa			
InCos-P	differential pressure, VAV sensors	± 100...	7.500 Pa			
ExCos-D	temperature and humidity transmitter for ExPro-C... sensors					
RedCos-D	temperature and humidity transmitter for ExPro-C... sensors					
InCos-D	temperature and humidity transmitter for InPro-C... sensors					
ExPro-C...	temperature and humidity sensors for operation in HVAC systems					
InPro-C...	temperature and humidity sensors for operation in HVAC systems					
ExLine	transmitter EXL-IM-9282-... for passive, potential free, analog ExSens sensors					
ExSens	analogue, passive temperature/humidity-/pressure sensors					
Switching sensors (thermostats, hygrostats, pressostats, fan belt protection, frost protection)						
Overview	switching (binary) sensors	0...	5.000 Pa			
ExBin-P	pressure/differential pressure	0...	5.000 Pa			
RedBin-P	pressure/differential pressure	0...	5.000 Pa			
InBin-P	pressure/differential pressure					
ExBin-FR	frost protection thermostat	-10...	+15 °C			
RedBin-FR	frost protection thermostat	-10...	+15 °C			
InBin-FR	frost protection thermostat	-10...	+15 °C			
ExBin-A	modules for adaptation of 1-5 passive, potential free, switching ExSens sensors					
RedBin-A	modules for adaptation of 1-5 passive, potential free, switching ExSens sensors					
InBin-A	modules for adaptation of 1-5 passive, potential free, switching sensors					
ExBin-D	temperature and humidity thermostat for ExPro-B... sensors					
RedBin-D	temperature and humidity thermostat for ExPro-B... sensors					
InBin-D	temperature and humidity thermostat for InPro-B... sensors					
ExPro-B...	thermostat/hygrostat sensors for operation in HVAC systems					
InPro-B...	thermostat/hygrostat sensors for operation in HVAC systems					
ExLine	switching module EXL-IR-9270-... for passive, potential free, switching ExSens sensors					
ExSens	switching, passive temperature/humidity-/pressure sensors					
Special options for sensors						
Overview	special options for sensors					
Overview	heating system ..Polar for sensors					
ExPolar/ExArctic	heating system for sensors' use in Ex areas down to -40/-60 °C					
InPolar/InArctic	heating system for sensors' use in safe area down to -40/-60 °C					
Door holder magnets						
ExMag	door holder magnets with 650, 1.300, 2.000 N force					
Components						
ExComp	different Ex-components, e.g. switches, push buttons, ...					

*SA = Safearea (□) = on request

Additional information

Product codes/definitions	50
Installation according to ATEX (Zone system)	52
Installation according to NEC500 (Division system, North America)	53
Valve automation	54
Certification information	56
Information about ATEX directives	58
Labelling of explosionproof equipment according to ATEX	59
Explosionproof information	60
Information about zones, explosion groups and temperature classes	61
Ex applications	62
Damper actuation focused	66

Explosion protection is safety, worldwide, in thousands of applications!



Since 1975 Schischek has supplied electric explosionproof products worldwide for heating, ventilation and air-conditioning, for industrial and offshore applications.

Schischek Explosionproof has become an important partner for consultants, public authorities, control companies, installers, OEM's and, not least of all, the end user.

As supplier of components, we have always considered it our duty to develop products in conjunction with other control equipment. Modern Ex equipment, reliable, proven and with "state of the art" technology.

Safety is Essential

With this motto we state that explosion protection is not a question of statistics or half hearted solutions but that 100% safety must be guaranteed at all times. Explosion protection means taking on responsibility.

There is no "Little Ex-protection"!

People have confidence in us as Ex protection specialists and in you as consultant, installer and contractor. All our Ex products are, therefore, type-examination certified, approved by and produced according to the very latest standards and regulations. According to type and kind of protection, our products are suitable for operation in Ex areas, zones 0, 1, 2, 20, 21 and 22, including gases, vapours, mists and dusts – of course in accordance with ATEX directives.

Heating, Ventilation, Air-Conditioning



Schischek supplies control companies and contractors in the Building Automation market. We have developed equipment which is compatible with nearly all control systems. By combining our products with conventional switching and control equipment, reliable high quality systems are implemented that conform to Ex protection standards. Some examples of use are fire and smoke dampers, paintspray areas, exhaust systems in chemical laboratories, battery rooms, sewage treatment plants, pumping stations etc.

Offshore, Onshore, Shipbuilding



Harsh environmental conditions and robust quality cause stringent design / construction requirements on components and materials. A fast closing electric actuator for fire / smoke dampers of less than 3 seconds is a requirement on oil and gas platforms as well as on FPSO's. After an intense development process including trials, a completely new concept in actuator engineering was produced.

Since, thousands of our actuators in special aluminium and stainless steel housings or with offshore/marine coating have been delivered and installed, moreover, the product range has been continuously enlarged and refined.

Chemical, Pharmaceutical, Car Industries




Whether you need air flow control in a pharmaceutical plant or temperature regulation of paint tanks in the car industry, we offer cost-effective solutions specifically designed for control integration. Ex protection is required for applications from paint spray shops to drying stations. System compatibility with all aspects of control facilitates integrated planning from design to completion. At the same time, safety and reliability increase in planning, installation, approval and operation. Since all equipment is maintenance-free, cost savings are realised.

Water Treatment Plants, Compressor Stations



In co-operation with valve and damper manufacturers, industrial control companies and contractors, Schischek products are in use worldwide. Our products are characterised by the "highest protection class, compact size and easy handling".

We can provide solutions to problems as far as Ex ventilation and precise temperature control in industrial plants are concerned.



Connected Services

Intelligent Asset Management (iAM) is a cloud-based system for intelligent Rotork actuators and the flow control equipment they operate. Effective asset management and maintenance are essential for maintaining site uptime.



Reliability Services

Reliability Services is a customisable approach to maintenance, with options that provide progressively increased levels of coverage and support. Our tailor-made programmes increase reliability and availability and allow customers to have flexibility about what services are most appropriate for them.



Field Services

Site Support

Benefit from our on-site support, from installation to emergency repairs.

Upgrade Solutions

Make sure your assets are prepared for the future with suitable upgrade options.

Valve Automation

Achieve precise and consistent flow control with automation of existing valves and replacement actuator/valve packages.

Spares

Maximise performance and reliability with genuine OEM spare parts.



Support Services

Technical Training

Our products and solutions are used in mission-critical applications and it is critical that any workforce is highly trained to ensure a safe and efficient plant. We provide advanced technical training from our strategically located facilities around the world.


Technical Support

We provide expert technical support exactly when you need it – trusted by global industries for over 60 years. Our technical experts draw on decades of our experience to provide you with the right answers and solutions.

Which Components Have to be Explosionproof?

In the diagram below, a typical air-handling system shows which equipment is allowed in the Ex area and which should only be placed in the safe area. The diagram does not claim to be complete.

If in doubt, please do not hesitate to consult us. We will advise you in any case. A brief discussion in the early stages of planning can avoid substantial costs in remedial work later and gives you the peace of mind that you have a safely installed operating system.



1

Quarter-turn actuators for dampers and valves

ExMax
RedMax

- 5...150 Nm
- 3...150 sec/90°
- On-off, 3-pos
- modulating
- with/without spring-return



2

Failsafe linear valve actuators

ExMax + LIN
RedMax + LIN

- 500...6.000 N
- 7,5...42 mm stroke
- 0,1...15 sec/mm
- On-off, 3-pos
- modulating
- with spring-return



3

Linear valve actuators

ExRun
RedRun

- 500...10.000 N
- 5...60 mm stroke
- 2...15 sec/mm
- On-off, 3-pos
- modulating



4

Temperature and humidity sensors


ExCos-D
RedCos-D

- -40°C...+125°C
- 0...100 %rH
- full range adjustable



You should be aware of the areas of installation where an explosive atmosphere may build up. Furthermore, you should have the responsible authority classify the relevant Ex zone and in combination with type and condition of the explosive medium, you should be able to select suitable explosionproof equipment.

With our products this is simple because all equipment is certified according to the highest safety standards – according to ATEX, of course!



5

Pressure/differential pressure sensors

ExCos-P
RedCos-P



- $\pm 100 \dots \pm 7.500 \text{ Pa}$
- full range adjustable

6

Filter monitoring, fan belt protection

ExBin-P
RedBin-P



- $0 \dots 5.000 \text{ Pa}$
- Pressure/Differential pressure
- Fan-belt protection
- Filter protection
- 1- or 2-stage switching point

7

Thermostats, humidists, Frost protection

ExBin-D
RedBin-D



- $!40^\circ\text{C} \dots +125^\circ\text{C}$
- $0 \dots 100 \% \text{rH}$
- 1- or 2-stage

ExBin-FR
RedBin-FR

- $!10^\circ\text{C} \dots +15^\circ\text{C}$
- Capillary: 3 m, 6 m
- 1-stage switching point

8

Controller

ExReg-V
Differential pressure



- $0 \dots 100 \text{ Pa (VAV)}$
- $0 \dots 300 \text{ Pa (VAV)}$
- $0 \dots 1.000 \text{ Pa (VAV)}$

Quarter-turn and rotary applications for damper control ...



- › Hazardous locations zone 1, 2, 21, 22
- › Fast spring-return time
- › Universal power supply
- › Stainless steel solution
- › Offshore/marine coated version
- › Easy installation
- › Compact dimensions

Overview ..Max quarter-turn actuators

Installation areas:

ExMax- actuators for use in hazardous locations zone 1, 2, 21, 22

RedMax- actuators for use in hazardous locations zone 2, 22

InMax- actuators for use in safe area

Application areas:

Ex/Red/InMax- for air and fire dampers, VAV control, ball valves, control dampers, ...

The actuator concept offers obvious advantages:

1. Small dimension, compact, easy installation, highest protection classes, cost effective
2. Universal power supply 24 to 240 Volt AC/DC, self adjustable
3. With or without spring-return (in acc. with type)
4. Robust aluminium housing, IP66 / IP67, optional in stainless steel
5. Integrated heater for low temperatures
6. Onsite adjustable motor running time
7. Application also possible into harsh environment (stainless steel or offshore/marine coated)
8. Integrated manual override
9. Useful accessories such as retrofit limit switches
10. Actuators are direct coupling

Actuators for air-dampers		ExMax-., RedMax-., InMax-..! turn actuators 90° actuators from 5 to 150 Nm, with or w/o spring-return (running time ~ 1, 3, 10, 20 s depending on type), for air-dampers.
Nm ExMax 	normal wiring 	
	normal wiring 	
	normal wiring 	
	normal wiring 	
	normal wiring 	
Safe area Ex area		ExMax-., RedMax-., InMax-..! turn actuators 90° actuators from 5 to 150 Nm, with or w/o spring-return (running time ~ 1, 3, 10, 20 s depending on type), for butterfly valves and other quarter-turn valves.

ExMax 90° Ex Quarter-Turn Actuators Size "S" for Zone 1, 2, 21, 22

Explosionproof		Features of ExMax-.. size S	
ExMax-..	Size S	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC, INMETRO, KOSHA, CCC, UL*, CSA*, *...-A version only		ExMax are, in acc. with type, for automation of air dampers, fire and smokedampers, volume control, as well as for ball valves, throttle valves and other quarter-turn armatures. Delivery: 1 actuator, ~ 1 m cable, Allen key for manual override, 4 screws.	• 24...240 VAC/DC self adaptable power supply • Up to 5 different running times adjustable on site • 95° angle of rotation (5° pretension) • 100% overload protected • Aluminium housing IP66, cable ~ 1 m • ! 40°C! 20°C for type...F1) upto +40°C/+50°C • Emergency manual override • Squared shaft connection 12 " 12 mm • Dimensions (H" W" D) 210 " 95 " 80 mm

Ex-d quarter-turn actuators without spring-return, 24 to 240 VAC/DC, for zone 1, 2, 21, 22

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
ExMax- 5.10	5 Nm/ 10 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	-	-	S
ExMax-15.30	15 Nm/ 30 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	-	-	S
ExMax- 5.10-S	5 Nm/ 10 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	S
ExMax-15.30-S	15 Nm/ 30 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	S
ExMax- 5.10-Y	5 Nm/ 10 Nm	7,5/15/30/60/120 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
ExMax-15.30-Y	15 Nm/ 30 Nm	7,5/15/30/60/120 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S

Ex-d quarter-turn actuators with spring-return, 24 to 240 VAC/DC, for zone 1, 2, 21, 22

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
ExMax-5.10- F	5 Nm/ 10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	-	-	S
ExMax- 15- F	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	-	-	S
ExMax-5.10-SF	5 Nm/ 10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	S
ExMax- 15-SF	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	S
ExMax-5.10-YF	5 Nm/ 10 Nm	7,5/15/30/60/120 sec.	~ 3 sec. / 10 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
ExMax- 15-YF	15 Nm	7,5/15/30/60/120 sec.	~ 3 sec. / 10 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
ExMax-5.10-BF	5 Nm/ 10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	S
ExMax- 15-BF	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	S

Ex-d quarter-turn actuators with fast spring-return for Offshore application, 24 to 240 VAC/DC, for zone 1, 2, 21, 22

Type	Torque	Running time 90°	Spring-return*	Control mode	Feedback	Features	Size
ExMax- 8- F1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	-	-	S
ExMax-15- F1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	-	-	S
ExMax- 8-SF1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches(5°/85°)	-	S
ExMax-15-SF1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches(5°/85°)	-	S
ExMax- 8-BF1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches(5°/85°)	ExPro-TT...connector	S
ExMax-15-BF1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches(5°/85°)	ExPro-TT...connector	S

*At low temperatures the spring-return time might vary. For further assistance please contact our sales team.

Accessories

Type	Description/Technical data
ExSwitch	External, adaptable, on site adjustable Ex-d auxiliary switch with 2 potential free contacts, adaptable to ExMax-.. actuators
ExBox-3P	Ex-e terminal box connectable to ExMax-.. actuators with 1 cable for On-off or 3-pos operation
ExBox-3P/SW	Ex-e terminal box connectable to ExMax-.. actuators with 1 cable for On-off or 3-pos operation + 2 cable for external aux. switches type ExSwitch
ExBox-Y/S	Ex-e terminal box connectable to ExMax-.. actuators with 2 cable, for modulating operation or 3-pos + integrated switches (HS)
ExBox-Y/S/SW	Ex-e terminal box connectable to ExMax-.. actuators with 2 cable, for modulating or 3-pos operation with feedback signal + 2 cable for external aux. switches
ExBox-BF	Ex-e terminal box connectable to ExMax-.. actuators with 1 cable, for all ExMax-...BF
ExBox-BF/SW	Ex-e terminal box connectable to ExMax-.. actuators with 1 cable, for all ExMax-...BF + 2 cable for external aux. switches type ExSwitch
MKK-S	Mounting bracket for ..Box-terminal boxes for direct coupling to ..Max-.. actuators size S
KB-S	Mounting clamp for round dampershaft Ø10 to 20 mm and squared shafts 10 to 16 mm, incl. bracket, connectable to all ExMax-.. size S
KB-A	Shaft connection for dampershafts Ø1/2", adaptable for all North American ..Max-.. actuators size S
HV-SKU, HV-SLU	Manual override, connectable to actuators size S. HV-SKU = short version, HV-SLU = long version for add. mounting of ..Box-..Switch
AR-12-xx	Squared reduction part from 12 " 12 mm to shafts with 11 mm (type AR-12-11), 10 mm (type AR-12-10), 8 mm (type AR-12-08)
ExPro-TT...	Safety temperature trigger for fire dampers, switching at 71°/72°C, with 1 m cable, suitable only for ExMax-../RedMax-...-BF actuators!
EXC-DS1/VA	Safety temperature sensor for duct mounting, potential free contact, switching at 70°C...160°C (10°C steps)
DWB-S	Angle rotation limiter for mounting on actuator size S (details on request)
Retrofit-Kit-S	Mechanical adaptation for mounting on ..Max actuators size S, required to replace a previous type EXT15...F1, EXT12...F16, EXT15... or EXT30..
ADS	Different adaptations for different valves available. Please don't hesitate to ask for technical solution

Special options and offshore kits see page 25

ExMax 90° Ex Quarter-Turn Actuators Size "M" for Zone 1, 2, 21, 22

Explosionproof		Features of ExMax... size M	
ExMax-..	Size M	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC, INMETRO, KOSHA, CCC, UL*, CSA*, *...Aversion only		ExMaxare, in acc. with type, for automation of air dampers, fire and smokedampers, volume control, as well as for ball valves, throttle valves and other quarter-turn armatures. Delivery: 1 actuator, ~ 1 mcable, Allen key for manual override, 4 screws.	• 24...240 VAC/DC self adaptable power supply • Up to 5 different running times adjustable on site • 95° angle of rotation (5° pretension) • 100% overload protected • Aluminiumhousing IP67, cable ~ 1 m • ! 40°C(! 20°C for type ...F3) upto +40°C/+50°C • Emergency manual override • Squared shaft connection 16 " 16 mm • Dimensions (H" W" D) 288 " 149 " 116 mm

Ex-d quarter-turn actuators without spring-return, 24 to 240 VAC/DC, for zone 1, 2, 21, 22

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
ExMax-50.75	50 Nm/ 75 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	-	-	M
ExMax- 100	100 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	-	-	M
ExMax- 150	150 Nm	40/60/90/120 sec.	-	On-off, 3-pos	-	-	M
ExMax-50.75-S	50 Nm/ 75 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
ExMax- 100-S	100 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
ExMax- 150-S	150 Nm	40/60/90/120 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
ExMax-50.75-Y	50 Nm/ 75 Nm	40/60/90/120/150 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
ExMax- 100-Y	100 Nm	40/60/90/120/150 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M

Ex-d quarter-turn actuators with spring-return, 24 to 240 VAC/DC, for zone 1, 2, 21, 22

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
ExMax-30- F	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
ExMax-50- F	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
ExMax-60- F	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
ExMax-30-SF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
ExMax-50-SF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
ExMax-60-SF	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
ExMax-30-YF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
ExMax-50-YF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
ExMax-30-BF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	M
ExMax-50-BF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	M
ExMax-60-BF	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	M

Ex-d quarter-turn actuators with fast spring-return for Offshore application, 24 to 240 VAC/DC, for zone 1, 2, 21, 22

Type	Torque	Running time 90°	Spring-return*	Control mode	Feedback	Features	Size
ExMax-30- F3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	-	-	M
ExMax-50- F3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	-	-	M
ExMax-30-SF3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	-	M
ExMax-50-SF3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	-	M
ExMax-30-BF3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	ExPro-TT...connector	M
ExMax-50-BF3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	ExPro-TT...connector	M

*At low temperatures the spring-return time might vary. For further assistance please contact our sales team.

Accessories

Type	Description/Technical data
ExSwitch	External, adaptable, on site adjustable Ex-d auxiliary switch with 2 potential free contacts, adaptable to ExMax... actuators
ExBox-3P	Ex-e terminal box connectable to ExMax... actuators with 1 cable for On-off or 3-pos operation
ExBox-3P/SW	Ex-e terminal box connectable to ExMax... actuators with 1 cable for On-off or 3-pos operation + 2 cable for external aux. switches type ExSwitch
ExBox-Y/S	Ex-e terminal box connectable to ExMax... actuators with 2 cable, for modulating operation or 3-pos + integrated switches (HS)
ExBox-Y/S/SW	Ex-e terminal box connectable to ExMax... actuators with 2 cable, for modulating or 3-pos operation with feedback signal + 2 cable for external aux. switches
ExBox-BF	Ex-e terminal box connectable to ExMax... actuators with 1 cable, for all ExMax...-BF
ExBox-BF/SW	Ex-e terminal box connectable to ExMax... actuators with 1 cable, for all ExMax...-BF + 2 cable for external aux. switches type ExSwitch
MKK-M	Mounting bracket for ..Box-terminal boxes for direct coupling to ..Max... actuators size M
HV-MU	Manual override, connectable to actuators size M
AR-16-xx	Squared reduction part from 16 " 16 mm to shafts with 14 mm (type AR-16-14), 12 mm (type AR-16-12)
ExPro-TT...	Safety temperature trigger for fire dampers, switching at 72°C, with 1 m cable, suitable only for ExMax.../RedMax...-BF actuators!
EXC-DS1/VA	Safety temperature sensor for duct mounting, potential free contact, switching at 70°C...160°C (10°C steps)
DWB-M	Angle rotation limiter for mounting on actuator size M
Retrofit-Kit-M	Mechanical adaptation for mounting on ..Max actuators size M, required to replace a previous type EXT30...F3, EXT50...F3 or EXT50...
ADM	Different adaptations for different valves available. Please don't hesitate to ask for technical solution

Special options and offshore kits see page 25

RedMax 90° Ex Quarter-Turn Actuators "S" for Zone 2, 22

Explosionproof		Features of RedMax-.. size S	
RedMax-.. Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC, INMETRO, CCC, UL*, CSA*, *...Aversion only	Size S 	Description RedMax are, in acc. with type, for automation of air dampers, fire and smokedampers, volume control, as well as for ball valves, throttle valves and other quarter-turn armatures. Delivery: 1 actuator, ~ 1 m cable, Allen key for manual override, 4 screws.	Basics • 24...240 VAC/DC self adaptable power supply • Up to 5 different running times adjustable on site • 95° angle of rotation (5° pretension) • 100% overload protected • Aluminium housing IP66, cable ~ 1 m • ! 40°C! 20°C for type...F1) upto +40°C/+50°C • Emergency manual override • Squared shaft connection 12 " 12 mm • Dimensions (H " W " D) 210 " 95 " 80 mm

Ex-d quarter-turn actuators without spring-return, 24 to 240 VAC/DC, for zone 2, 22

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
RedMax- 5.10	5 Nm/10 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	-	-	S
RedMax-15.30	15 Nm/30 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	-	-	S
RedMax- 5.10-S	5 Nm/10 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	S
RedMax-15.30-S	15 Nm/30 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	S
RedMax- 5.10-Y	5 Nm/10 Nm	7,5/15/30/60/120 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
RedMax-15.30-Y	15 Nm/30 Nm	7,5/15/30/60/120 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S

Ex-d quarter-turn actuators with spring-return, 24 to 240 VAC/DC, for zone 2, 22

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
RedMax-5.10- F	5 Nm/10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	-	-	S
RedMax- 15- F	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	-	-	S
RedMax-5.10-SF	5 Nm/10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	S
RedMax- 15-SF	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	S
RedMax-5.10-YF	5 Nm/10 Nm	7,5/15/30/60/120 sec.	~ 3 sec. / 10 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
RedMax- 15-YF	15 Nm	7,5/15/30/60/120 sec.	~ 3 sec. / 10 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
RedMax-5.10-BF	5 Nm/10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	S
RedMax- 15-BF	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	S

Ex-d quarter-turn actuators with fast spring-return for Offshore application, 24 to 240 VAC/DC, for zone 2, 22

Type	Torque	Running time 90°	Spring-return*	Control mode	Feedback	Features	Size
RedMax- 8- F1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	-	-	S
RedMax-15- F1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	-	-	S
RedMax- 8-SF1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches(5°/85°)	-	S
RedMax-15-SF1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches(5°/85°)	-	S
RedMax- 8-BF1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches(5°/85°)	ExPro-TT...connector	S
RedMax-15-BF1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches(5°/85°)	ExPro-TT...connector	S

*At low temperatures the spring-return time might vary. For further assistance please contact our sales team.

Accessories

Type	Description/Technical data
RedSwitch	External, adaptable, on site adjustable auxiliary switch with 2 potential free contacts, adaptable to RedMax-.. actuators
RedBox-3P	Ex-e terminal box connectable to RedMax-.. actuators with 1 cable for On-off or 3-pos operation
RedBox-3P/SW	Ex-e terminal box connectable to RedMax-.. actuators with 1 cable for On-off or 3-pos operation + 2 cable for external aux. switches type RedSwitch
RedBox-Y/S	Ex-e terminal box connectable to RedMax-.. actuators with 2 cable, for modulating operation or 3-pos + integrated switches (HS)
RedBox-Y/S/SW	Ex-e terminal box connectable to RedMax-.. actuators with 2 cable, for modulating or 3-pos operation with feedback signal + 2 cable for external aux. switches
RedBox-BF	Ex-e terminal box connectable to RedMax-.. actuators with 1 cable, for all RedMax-...-BF
RedBox-BF/SW	Ex-e terminal box connectable to RedMax-.. actuators with 1 cable, for all RedMax-...-BF + 2 cable for external aux. switches type RedSwitch
MKK-S	Mounting bracket for ..Box-terminal boxes for direct coupling to ..Max-.. actuators size S
KB-S	Mounting clamp for round dampershaft Ø10 to 20 mm and squared shafts 10 to 16 mm, incl. bracket, connectable to all RedMax-.. size S
KB-A	Shaft connection for dampershafts Ø1½", adaptable for all North American ..Max-.. actuators size S
HV-SKU, HV-SLU	Manual override, connectable to actuators size S. HV-SKU = short version, HV-SLU = long version for add. mounting of ..Box../Switch
AR-12-xx	Squared reduction part from 12 " 12 mm to shafts with 11 mm (type AR-12-11), 10 mm (type AR-12-10), 8 mm (type AR-12-08)
ExPro-TT...	Safety temperature trigger for fire dampers, switching at 71°/72°C, with 1 m cable, suitable only for ExMax-../RedMax-...-BF actuators!
EXC-DS1/VA	Safety temperature sensor for duct mounting, potential free contact, switching at 70°C...160°C (10°C steps)
DWB-S	Angle rotation limiter for mounting on actuator size S (details on request)
Retrofit-Kit-S	Mechanical adaptation for mounting on ..Max actuators size S, required to replace a previous type EXT15...-F1, EXT12...-F16, EXT15... or EXT30..
ADS	Different adaptations for different valves available. Please don't hesitate to ask for technical solution

Special options and offshore kits see page 25

RedMax 90° Ex Quarter-Turn Actuators "M" for Zone 2, 22

Explosionproof		Features of RedMax-.. size M	
RedMax-..	Size M	Description	Basics
Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC, INMETRO, CCC, UL*, CSA*, *...Aversion only		RedMax are, in acc. with type, for automation of air dampers, fire and smoke dampers, volume control, as well as for ball valves, throttle valves and other quarter-turn armatures. Delivery: 1 actuator, ~ 1 m cable, Allen key for manual override, 4 screws.	• 24...240 VAC/DC self adaptable power supply • Up to 5 different running times adjustable on site • 95° angle of rotation (5° pretension) • 100% overload protected • Aluminium housing IP67, cable ~ 1 m • ! 40°C! 20°C for type...F3) upto +40°C/+50°C • Emergency manual override • Squared shaft connection 16 " 16 mm • Dimensions {H" W" D} 288 " 149 " 116 mm

Ex-d quarter-turn actuators without spring-return, 24 to 240 VAC/DC, for zone 2, 22

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
RedMax-50.75	50 Nm/ 75 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	-	-	M
RedMax- 100	100 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	-	-	M
RedMax- 150	150 Nm	40/60/90/120 sec.	-	On-off, 3-pos	-	-	M
RedMax-50.75-S	50 Nm/ 75 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
RedMax- 100-S	100 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
RedMax- 150-S	150 Nm	40/60/90/120 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
RedMax-50.75-Y	50 Nm/ 75 Nm	40/60/90/120/150 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
RedMax- 100-Y	100 Nm	40/60/90/120/150 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M

Ex-d quarter-turn actuators with spring-return, 24 to 240 VAC/DC, for zone 2, 22

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
RedMax-30- F	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
RedMax-50- F	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
RedMax-60- F	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
RedMax-30-SF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
RedMax-50-SF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
RedMax-60-SF	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
RedMax-30-YF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
RedMax-50-YF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
RedMax-30-BF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	M
RedMax-50-BF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	M
RedMax-60-BF	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	ExPro-TT...connector	M

Ex-d quarter-turn actuators with fast spring-return for Offshore application, 24 to 240 VAC/DC, for zone 2, 22

Type	Torque	Running time 90°	Spring-return*	Control mode	Feedback	Features	Size
RedMax-30- F3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	-	-	M
RedMax-50- F3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	-	-	M
RedMax-30-SF3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	-	M
RedMax-50-SF3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	-	M
RedMax-30-BF3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	ExPro-TT...connector	M
RedMax-50-BF3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	ExPro-TT...connector	M

*At low temperatures the spring-return time might vary. For further assistance please contact our sales team.

Accessories

Type	Description/Technical data
RedSwitch	External, adaptable, on site adjustable auxiliary switch with 2 potential free contacts, adaptable to RedMax-.. actuators
RedBox-3P	Ex-e terminal box connectable to RedMax-.. actuators with 1 cable for On-off or 3-pos operation
RedBox-3P/SW	Ex-e terminal box connectable to RedMax-.. actuators with 1 cable for On-off or 3-pos operation + 2 cable for external aux. switches type RedSwitch
RedBox-Y/S	Ex-e terminal box connectable to RedMax-.. actuators with 2 cable, for modulating operation or 3-pos + integrated switches (HS)
RedBox-Y/S/SW	Ex-e terminal box connectable to RedMax-.. actuators with 2 cable, for modulating or 3-pos operation with feedback signal + 2 cable for external aux. switches
RedBox-BF	Ex-e terminal box connectable to RedMax-.. actuators with 1 cable, for all RedMax-...-BF
RedBox-BF/SW	Ex-e terminal box connectable to RedMax-.. actuators with 1 cable, for all RedMax-...-BF + 2 cable for external aux. switches type RedSwitch
MKK-M	Mounting bracket for ..Box-terminal boxes for direct coupling to ..Max-.. actuators size M
HV-MU	Manual override, connectable to actuators size M
AR-16-xx	Squared reduction part from 16 " 16 mm to shafts with 14 mm (type AR-16-14), 12 mm (type AR-16-12)
ExPro-TT...	Safety temperature trigger for fire dampers, switching at 72°C, with 1 m cable, suitable only for ExMax-../RedMax-...-BF actuators!
EXC-DS1/A	Safety temperature sensor for duct mounting, potential free contact, switching at 70°C...160°C (10°C steps)
DWB-M	Angle rotation limiter for mounting on actuator size M
Retrofit-Kit-M	Mechanical adaptation for mounting on ..Max actuators size M, required to replace a previous type EXT30...F3, EXT50...F3 or EXT50...
ADM	Different adaptations for different valves available. Please don't hesitate to ask for technical solution

Special options and offshore kits see page 25

InMax 90° Quarter-Turn Actuators "S" for Safe Area

Industrial		Features of InMax-.. size S	
InMax-..	Size S	Description	Basics
NOTE: Explosion proof and only for use in safe area IP66 		InMax are, in acc. with type, for automation of air dampers, fire and smokedampers, volume control, as well as for ball valves, throttle valves and other quarter-turn armatures. Delivery: 1 actuator, ~ 1 m cable, Allen key for manual override, 4 screws.	• 24...240 VAC/DC self adaptable power supply • Up to 5 different running times adjustable on site • 95° angle of rotation (5° pretension) • 100% overload protected • Aluminium housing IP66, cable ~ 1 m • ! 40°C (! 20°C for type...F1) upto +50°C • Emergency manual override • Squared shaft connection 12 " 12 mm • Dimensions (H " W " D) 210 " 95 " 80 mm

Quarter-turn actuators without spring-return, 24 to 240 VAC/DC, for safe area

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
InMax- 5.10	5 Nm/10 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	-	-	S
InMax-15.30	15 Nm/30 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	-	-	S
InMax- 5.10-S	5 Nm/10 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	2 " aux. switches (5°/85°)	-	S
InMax-15.30-S	15 Nm/30 Nm	3/15/30/60/120 sec.	-	On-off, 3-pos	2 " aux. switches (5°/85°)	-	S
InMax- 5.10-Y	5 Nm/10 Nm	7,5/15/30/60/120 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
InMax-15.30-Y	15 Nm/30 Nm	7,5/15/30/60/120 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S

Quarter-turn actuators with spring-return, 24 to 240 VAC/DC, for safe area

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
InMax-5.10-F	5 Nm/10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	-	-	S
InMax- 15-F	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	-	-	S
InMax-5.10-SF	5 Nm/10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches (5°/85°)	-	S
InMax- 15-SF	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches (5°/85°)	-	S
InMax-5.10-YF	5 Nm/10 Nm	7,5/15/30/60/120 sec.	~ 3 sec. / 10 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
InMax- 15-YF	15 Nm	7,5/15/30/60/120 sec.	~ 3 sec. / 10 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	S
InMax-5.10-BF	5 Nm/10 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches (5°/85°)	InPro-TT...connector	S
InMax- 15-BF	15 Nm	3/15/30/60/120 sec.	~ 3 sec. / 10 sec.	On-off, 3-pos	2 " aux. switches (5°/85°)	InPro-TT...connector	S

Quarter-turn actuators with fast spring-return for Offshore application, 24 to 240 VAC/DC, for safe area

Type	Torque	Running time 90°	Spring-return*	Control mode	Feedback	Features	Size
InMax- 8-F1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	-	-	S
InMax-15-F1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	-	-	S
InMax- 8-SF1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches (5°/85°)	-	S
InMax-15-SF1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches (5°/85°)	-	S
InMax- 8-BF1	6 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches (5°/85°)	InPro-TT...connector	S
InMax-15-BF1	12 Nm	3/15/30/60/120 sec.	~ 1 sec.	On-off	2 " aux. switches (5°/85°)	InPro-TT...connector	S

*At low temperatures the spring-return time might vary. For further assistance please contact our sales team.

Accessories

Type	Description/Technical data
InSwitch	External, adaptable, on site adjustable auxiliary switch with 2 potential free contacts, adaptable to InMax-.. actuators
InBox-3P	Terminal box connectable to InMax-.. actuators with 1 cable for On-off or 3-pos operation
InBox-3P/SW	Terminal box connectable to InMax-.. actuators with 1 cable for On-off or 3-pos operation + 2 cable for external aux. switches type InSwitch
InBox-Y/S	Terminal box connectable to InMax-.. actuators with 2 cable, for modulating operation or 3-pos + integrated switches (HS)
InBox-Y/S/SW	Terminal box connectable to InMax-.. actuators with 2 cable, for modulating or 3-pos operation with feedback signal + 2 cable for external aux. switches
InBox-BF	Terminal box connectable to InMax-.. actuators with 1 cable, for all InMax-...-BF
InBox-BF/SW	Terminal box connectable to InMax-.. actuators with 1 cable, for all InMax-...-BF + 2 cable for external aux. switches type InSwitch
MKK-S	Mounting bracket for ..Box-terminal boxes for direct coupling to ..Max-.. actuators size S
KB-S	Mounting clamp for round damper shaft Ø10 to 20 mm and squared shafts 10 to 16 mm, ind. bracket, connectable to all InMax-.. size S
KB-A	Shaft connection for damper shafts Ø1½", adaptable for all North American ..Max-.. actuators size S
HV-SKU, HV-SLU	Manual override, connectable to actuators size S. HV-SKU = short version, HV-SLU = long version for add. mounting of ..Box/..Switch
AR-12-xx	Squared reduction part from 12 " 12 mm to shafts with 11 mm (type AR-12-11), 10 mm (type AR-12-10), 8 mm (type AR-12-08)
InPro-TT-...	Safety temperature trigger for fire dampers, switching at 71°/72°C, with 1 m cable, suitable only for InMax-...-BF actuators!
EXC-DS1/VA	Safety temperature sensor for duct mounting, potential free contact, switching at 70°C...160°C (10°C steps)
DWB-S	Angle rotation limiter for mounting on actuator size S (details on request)
Retrofit-Kit-S	Mechanical adaptation for mounting on ..Max actuators size S, required to replace a previous type NOT15...F1, NOT12...F16, NOT15...or NOT30..
ADS	Different adaptations for different valves available. Please don't hesitate to ask for technical solution

Special options and offshore kits see page 25

InMax 90° Quarter-Turn Actuators "M" for Safe Area

Industrial		Features of InMax-.. size M	
InMax-..	Size M	Description	Basics
NOTE: Explosion proof and only for use in safe area IP67		InMax are, in acc. with type, for automation of air dampers, fire and smokedampers, volume control, as well as for ball valves, throttle valves and other quarter-turn armatures. Delivery: 1 actuator, ~ 1 m cable, Allen key for manual override, 4 screws.	• 24...240 VAC/DC self adaptable power supply • Up to 5 different running times adjustable on site • 95° angle of rotation (5° pretension) • 100% overload protected • Aluminium housing IP67, cable ~ 1 m • ! 40°C! 20°C for type...F3) upto +50°C • Emergency manual override • Squared shaft connection 16 " 16 mm • Dimensions {H" W" D} 288 " 149 " 116 mm

Quarter-turn actuators without spring-return, 24 to 240 VAC/DC, for safe area

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
InMax-50.75	50 Nm/75 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	-	-	M
InMax- 100	100 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	-	-	M
InMax- 150	150 Nm	40/60/90/120 sec.	-	On-off, 3-pos	-	-	M
InMax-50.75-S	50 Nm/75 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
InMax- 100-S	100 Nm	40/60/90/120/150 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
InMax- 150-S	150 Nm	40/60/90/120 sec.	-	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
InMax-50.75-Y	50 Nm/75 Nm	40/60/90/120/150 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
InMax- 100-Y	100 Nm	40/60/90/120/150 sec.	-	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M

Quarter-turn actuators with spring-return, 24 to 240 VAC/DC, for safe area

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
InMax-30- F	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
InMax-50- F	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
InMax-60- F	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	-	-	M
InMax-30-SF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
InMax-50-SF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
InMax-60-SF	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	-	M
InMax-30-YF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
InMax-50-YF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	3-pos, 0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	-	M
InMax-30-BF	30 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	InPro-TF..connector	M
InMax-50-BF	50 Nm	40/60/90/120/150 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	InPro-TF..connector	M
InMax-60-BF	60 Nm	40/60/90/120 sec.	~ 20 sec.	On-off, 3-pos	2 " aux. switches(5°/85°)	InPro-TF..connector	M

Quarter-turn actuators with fast spring-return for Offshore application, 24 to 240 VAC/DC, for safe area

Type	Torque	Running time 90°	Spring-return*	Control mode	Feedback	Features	Size
InMax-30- F3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	-	-	M
InMax-50- F3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	-	-	M
InMax-30-SF3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	-	M
InMax-50-SF3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	-	M
InMax-30-BF3	24 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	InPro-TF..connector	M
InMax-50-BF3	40 Nm	40/60/90/120/150 sec.	~ 3 sec.	On-off	2 " aux. switches(5°/85°)	InPro-TF..connector	M

*At low temperatures the spring-return time might vary. For further assistance please contact our sales team.

Accessories

Type	Description/Technical data
InSwitch	External, adaptable, on site adjustable auxiliary switch with 2 potential free contacts, adaptable to InMax-.. actuators
InBox-3P	Terminal box connectable to InMax-.. actuators with 1 cable for On-off or 3-pos operation
InBox-3P/SW	Terminal box connectable to InMax-.. actuators with 1 cable for On-off or 3-pos operation + 2 cable for external aux. switches type InSwitch
InBox-Y/S	Terminal box connectable to InMax-.. actuators with 2 cable, for modulating operation or 3-pos + integrated switches (HS)
InBox-Y/S/SW	Terminal box connectable to InMax-.. actuators with 2 cable, for modulating or 3-pos operation with feedback signal + 2 cable for external aux. switches
InBox-BF	Terminal box connectable to InMax-.. actuators with 1 cable, for all InMax-...-BF
InBox-BF/SW	Terminal box connectable to InMax-.. actuators with 1 cable, for all InMax-...-BF + 2 cable for external aux. switches type InSwitch
MKK-M	Mounting bracket for ..Box-terminal boxes for direct coupling to ..Max-.. actuators size M
HV-MU	Manual override, connectable to actuators size M
AR-16-xx	Squared reduction part from 16 " 16 mm to shafts with 14 mm (type AR-16-14), 12 mm (type AR-16-12)
InPro-TF...	Safety temperature trigger for fire dampers, switching at 72°C, with 1 m cable, suitable only for InMax-...-BF actuators!
EXC-DS1/A	Safety temperature sensor for duct mounting, potential free contact, switching at 70°C...160°C (10°C steps)
DWB-M	Angle rotation limiter for mounting on actuator size M
Retrofit-Kit-M	Mechanical adaptation for mounting on ..Max actuators size M, required to replace a previous type NOT30...F3, NOT50...F3 or NOT50..
ADM	Different adaptations for different valves available. Please don't hesitate to ask for technical solution

Special options and offshore kits see page 25

Linear applications for valve control ...



- › Hazardous locations zone 1, 2, 21, 22
- › Fast spring-return time
- › Universal power supply
- › Offshore/marine coated version
- › Easy installation
- › Robust IP66 housing
- › Compact dimensions

Overview ..Max + LIN linear guide unit and ..Run valve actuators

Installation areas:

ExMax-...+LIN, ExRun-... actuators for use in hazardous locations zone 1, 2, 21, 22

RedMax-...+LIN, RedRun-... actuators for use in hazardous locations zone 2, 22

InMax-...+LIN, InRun-... actuators for use in safe area


Application areas:

Ex/Red/InMax + LIN for globe- or 3-way valves (with safety function)

Ex/Red/InRun for globe- or 3-way valves

The actuator concept offers obvious advantages:

1. Small dimension, compact, easy installation, highest protection classes, cost effective
2. Universal power supply 24 to 240 Volt AC/DC, self adjustable
3. With or without spring-return (spring-return only at ..Max + LIN linear guide unit)
4. Robust aluminium housing, IP66
5. Integrated heater for low temperatures
6. Onsite adjustable motor running time
7. Integrated manual override
8. Offshore/marine coated version available
9. Useful accessories such as retrofit limit switches



..Max-.. + LIN-.. Linear Valve Actuators Size "S" and "M" with Spring-Return

Explosionproof		Industrial	Features ..Max-.. + LIN-.. (size S and M)	
ExMax-.. + LIN-..	RedMax-.. + LIN-..	InMax-.. + LIN-..	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC, INMETRO, KOSHA¹ ¹ExMax size only UL*, CSA* *...Aversion only 	Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC, INMETRO UL*, CSA* *...Aversion only 	NOT Explosionproof and only for use in safe area IP66 	..Max-.. + LIN-.. linear valve actuators with spring-return for automation of globe or 3-way valves. Use as actuator with safety function, On-off or 3-pos. actuator or modulating actuator. Delivery: Linear unit, suitable for all ..Max-..-F actuators size S or M. Required accessories: Valve adaptation in accordance with valve manufacturer, type and nominal size (diameter), terminal box, mounting bracket. Ordering example: Modulating valve actuator with spring-return in Ex area zone 2, for a globe valve with 20 mm stroke and a required force of 1.500 N. Actuator: RedMax-30-YF Linear adaptation: LIN-20 Valve adaptation: suitable for valve type on requ. Required: External box (RedBox-Y/S) Required: Mounting bracket (MKK-M)	• 24...240 VAC/DC self adaptable power supply • Running time 0,1...15 sec/mm% • Stroke 7,5, 10, 15, 20, 30, 42 mm% • Force 500...3.000 N% • Spring-return 3/10 sec. (size S), 20 sec. (size M) % • Control mode On-off, 3-pos., 0-10 VDC, 4-20 mA % • Aluminium housing, IP66 ² • Ambient temperature! 20...+40 °C (T6), ! 20...+50 °C (T5) • Weight (incl. actuator) ~ 8 kg (size S), ~ 14 kg (size M) % • External terminal box optional ² %inacc. with type I ² applies for actuator

Linear unit for actuators with spring-return, 24 to 240 VAC/DC

Type	Stroke (max.)	Description
LIN-7,5	7,5 mm	Linear unit up to max. 7,5 mm stroke, suitable for all ..Max-...-F actuators size S or M with spring-return
LIN-10	10 mm	Linear unit up to max. 10 mm stroke, suitable for all ..Max-...-F actuators size S or M with spring-return
LIN-15	15 mm	Linear unit up to max. 15 mm stroke, suitable for all ..Max-...-F actuators size S or M with spring-return
LIN-20	20 mm	Linear unit up to max. 20 mm stroke, suitable for all ..Max-...-F actuators size S or M with spring-return
LIN-30	30 mm	Linear unit up to max. 30 mm stroke, suitable for all ..Max-...-F actuators size S or M with spring-return
LIN-40	42 mm	Linear unit up to max. 42 mm stroke, suitable for all ..Max-...-F actuators size M with spring-return

Additional price for adaptation, dependent on valve manufacturer, valve type and stroke.

LIN Special Options for Linear Unit Suitable for Actuators

Explosionproof/Safe area		Features LIN-....CT	
LIN-....CT	Special options	Description	Basics
available for linear unit LIN-.. In accordance with ..Max type for use in Ex area or safe area		CT version with aluminium housing and offshore/marine coating, resistant against corrosive and maritime atmosphere, some parts nickel plated. Delivery: 1 linear unit with special option Ordering example: LIN-20-CT	CT: • Offshore/marine coated aluminium housing • Resistant against corrosive and/or maritime atmosphere

LIN-.. options

Type	Description/Technical data
LIN-....CT	Offshore/marine coated aluminium housing, resistant against corrosive and/or maritime atmosphere. Lifting rod, connecting parts and screws in VA (surcharge)
ADLIN	Different adaptations for different valves available. Please don't hesitate to ask for technical solution

Additional price for adaptation in stainless steel (VA) for CT version.

..Max-.. + LIN-.. Linear Valve Actuators Size "S" and "M" with Spring-Return

Mounting variations				Valve adaptation
				To select the right valve adaptation and get the right price information the following data are required: 1. Valve manufacturer 2. Valve type 3. Valve nominal size (diameter) DN For adaptations which are already designed by Schischek this information is sufficient. To design new adaptations we need additional details of the valve body as well as drawings. With the purchase order you have to provide actuator and valve type.

Selection of recommended actuators in relation of force and max. stroke

Type	LIN- 7.5	LIN- 10	LIN- 15	LIN- 20	LIN- 30	LIN- 40	
max. stroke	7.5 mm	10 mm	15 mm	20 mm	30 mm	42 mm	
Force							
500 N	...Max- 15- ...F	...Max- 15- ...F	...Max- 15- ...F	...Max- 15- ...F	...Max- 15- ...F	...Max- 30- ...F	At strokes between two values use the next higher linear unit e.g. 24 mm stroke = LIN-30
800 N					...Max- 30- ...F		
1.000 N			...Max- 30- ...F	...Max- 30- ...F	...Max- 50- ...F	...Max- 50- ...F	
1.500 N							
2.000 N	...Max- 30- ...F	...Max- 30- ...F	...Max- 30- ...F	...Max- 50- ...F	—		
2.500 N				...Max- 50- ...F	—	—	
3.000 N							

Attention: Limitation of resolution at YF-actuators with strokes < nominal (motor blockade)!

Note the maximum force of the actuator to prevent damage to your valve!

Info: Suitable actuators with spring-return see page 12-17.

1

Nominal force (N) at spring of actuator in relation of max. stroke of LIN at temperatures between !20...+40 °C

Type	LIN- 7.5	LIN- 10	LIN- 15	LIN- 20	LIN- 30	LIN- 40	
...Max- 15- ...F	1.500	1.500	1.000	800	500	—	Blocking force in motor is round about 3 to 4 times larger than nominal force. Note valve dimensioning!
...Max- 30- ...F	3.000	3.000	2.000	1.500	1.000	800	
...Max- 50- ...F	—	—	3.000	3.000	2.000	1.500	

Attention: Limitation of resolution at YF-actuators with strokes < nominal (motor blockade)!

Note the maximum force of the actuator to prevent damage to your valve!

2

Nominal force (N) at spring of actuator in relation of max. stroke of LIN at temperatures between 0...+40°C


Type	LIN- 7.5	LIN- 10	LIN- 15	LIN- 20	LIN- 30	LIN- 40	
...Max- 15- ...F	3.000	3.000	2.000	1.600	1.000	—	Blocking force in motor is round about 1.5 to 2 times larger than nominal force. Note valve dimensioning!
...Max- 30- ...F	6.000	6.000	4.000	3.000	2.000	1.600	
...Max- 50- ...F	—	—	6.000	6.000	4.000	3.000	

Attention: Above mentioned values are nominal trusts with performed self adjustment drive!

The maximum trusts can read values which are up to three to four times higher than values of tables!

Without performed self adjustment drive there can occur much higher trust values, which can cause damages on the mentioned valve or linkages!

Spring-return time depends on the effective required thrust and can exceed standard values!



ExRun/RedRun/InRun Valve Actuators

Explosionproof		Industrial	Features of ExRun-.., RedRun-.., InRun-..	
ExRun-..	RedRun-..	InRun-..	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC, INMETRO, KOSHA, CCC, UL*, CSA* *...Aversion only	Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC, INMETRO, KOSHA, CCC, UL*, CSA* *...Aversion only	NOTE: Explosionproof and only for use in safe area IP66	ExRun-.., RedRun-.. and InRun-.. valve actuators are used for automation of 2- and 3-way valves with 3-pos. on-off or modulating mode. Delivery: 1 actuator with integrated Ex-e terminal box, Emergency manual override. Required accessories: Valve adaptation in accordance with valve manufacturer, type and nominal size (diameter).	• 24...240 VAC/DC self adaptable power supply • Up to 5 different running times adjustable on site • 5 to 60 mm stroke, mechanical limitation on each position • Automatic adaptation of modulating signal at Ex-, Red-, InRun-...-Y. • Aluminium housing IP66, integrated terminal box • ! 20...+40°C/+50°C, integrated heater • Emergency manual override • Dimension (H¹"W"D) 260¹ " 208 " 115 mm (without valve and adaptation) • Approximate weight 7.3...7.7 kg² (without valve and adaptation) ¹Height varies depending on type ²Weight varies depending on type
				

Ex-d valve actuators without spring-return for zone 1, 2, 21, 22

Type	Force	Running time	Spring-return	Control mode	Feedback	Stroke	Size
ExRun- 5.10	500 / 1.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
ExRun-25.50	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
ExRun-75.100	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
ExRun- 5.10 -Y	500 / 1.000 N	2/3/6/9/12 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
ExRun-25.50 -Y	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
ExRun-75.100-Y	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
ExRun- 5.10 -U	500 / 1.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S
ExRun-25.50 -U	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S
ExRun-75.100-U	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S

Ex-d valve actuators without spring-return for zone 2, 22

Type	Force	Running time	Spring-return	Control mode	Feedback	Stroke	Size
RedRun- 5.10	500 / 1.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
RedRun-25.50	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
RedRun-75.100	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
RedRun- 5.10 -Y	500 / 1.000 N	2/3/6/9/12 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
RedRun-25.50 -Y	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
RedRun-75.100-Y	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
RedRun- 5.10 -U	500 / 1.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S
RedRun-25.50 -U	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S
RedRun-75.100-U	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S

Valve actuators without spring-return for safe area

Type	Force	Running time	Spring-return	Control mode	Feedback	Stroke	Size
InRun- 5.10	500 / 1.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
InRun-25.50	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
InRun-75.100	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	On-off, 3-pos	-	5...60 mm	S
InRun- 5.10 -Y	500 / 1.000 N	2/3/6/9/12 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
InRun-25.50 -Y	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
InRun-75.100-Y	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	0...10 VDC, 4...20 mA	0...10 VDC, 4...20 mA	5...60 mm	S
InRun- 5.10 -U	500 / 1.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S
InRun-25.50 -U	2.500 / 5.000 N	2/3/6/9/12 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S
InRun-75.100-U	7.500 / 10.000 N	4/6/9/12/15 sec/mm	-	On-off, 3-pos	0...10 VDC, 4...20 mA	5...60 mm	S

Accessories

Type	Description/Technical data
ExSwitch-R-L	External, adaptable, on site adjustable Ex-d auxiliary switch linear for Ex/RedRun-.. with 2 potential free contacts, additionally Ex-e terminal box + mounting bracket necessary
InSwitch- R-L	External, adaptable, on site adjustable auxiliary switch linear for InRun-.. with 2 potential free contacts, additionally terminal box + mounting bracket necessary
ExBox- SW	Ex-e terminal box suitable for ExRun.. valve-actuators with external switches ExSwitch-R-L
RedBox-SW	Ex-e terminal box suitable for RedRun.. valve-actuators with external switches ExSwitch-R-L
InBox- SW	Terminal box suitable for InRun.. valve-actuators with external switches InSwitch-R-L
MKK-S	Mounting-brackets suitable for ..Box-terminal boxes for direct mounting on ..Run actuators size S
HV-R	Manual override suitable for ..Run valve actuators size S
GMB-1	Rubber bellow up to 60 mm, colour black
ADR	Different adaptations for different valves available. Please don't hesitate to ask for technical solution

Special options and offshore kits see page 25

Required data for valve adaptation

To select the right valve adaptation and get the right price information the following data are required:

1. Valve manufacturer
2. Valve type
3. Valve nominal size (diameter) DN

For adaptations which are already designed by Schischek this information is sufficient.

To design new adaptations we need additional details of the valve body as well as drawings.

With the purchase order you have to provide actuator and valve type.

...Run + valve adaptation


ExRun-...

RedRun-...

InRun-...



Adaption




Overview of special options of Schischek actuators for use under extreme weather conditions

Application area:

Usage in hazardous locations under extreme weather conditions and/or for offshore/onshore applications.

Advantages:

- Resistant against corrosive and/or maritime atmosphere
- Usage under extreme weather conditions
- Approved for offshore-/onshore applications
- Robust and thereby extended period of application time of actuators

Special options quarter-turn actuators size S		
VAS CTS	..Max-.. S	normal wiring  VAS CTS ..Max-..! turn actuators size S Housing material in stainless steel (VAS) or aluminium housing with offshore/marine coating (CTS) for use under extreme weather conditions.
Special options quarter-turn actuators size M		
VAM CTM	..Max-.. M	normal wiring  VAM CTM ..Max-..! turn actuators size M Housing material in stainless steel (VAM) or aluminium housing with offshore/marine coating (CTM) for use under extreme weather conditions.
Special options valve actuators		
CTS	..Run-..	normal wiring  CTS ..Run-.. valve actuators Aluminium housing with offshore/marine coating (CTS) for use under extreme weather conditions.
Weather shield for quarter-turn and valve actuators		
WS-S WS-M WS-R	..Max-.. S/M ..Run-..	normal wiring  WS-S WS-M WS-R ..Max-..! turn and ..Run valve actuators Weather shield made of stainless steel for protection against weather influences like rain, sun or snow.
Safe area		Ex area
Further special features on request		
		• Connection technology and cable fittings • Special model for temperature range, runtime, corrosion protection, certification, ... • Special accessories, for e.g. indicators • Special features, e.g. > 90° angle of rotation or rotary variants

..Max Special Options for Quarter-Turn Actuators Size S or M

Explosionproof		Features ..Max-...VA/CT	
..Max-...VA/CT	Special options	Description	Basics
available for ExMax, RedMax and InMax In accordance with type for use in Ex area or safe area		VA version with housing material in stainless steel similar AISI 316, some parts nickel plated. CT version with aluminium housing and offshore/ marine coating, resistant against corrosive and maritime atmosphere, some parts nickel plated. Delivery: 1 quarter-turn actuator size S or M with special option Ordering example: ExMax-15.30-VAS	VA: - Housing material in stainless steel similar AISI 316, some parts nickel plated, screws in stainless steel CT: - offshore/ marine coated aluminium housing, resistant against corrosive and/ or maritime atmosphere - Cable glands brass nickel plated - Screws in stainless steel For general basics see ..Max quarter-turn actuators.

..Max-... options

Type	Description/Technical data
..Max-...- VAS	Housing material of ..Max quarter-turn actuator size S in stainless steel similar AISI 316, some parts nickel plated (surcharge)
..Max-...- VAM	Housing material of ..Max quarter-turn actuator size M in stainless steel similar AISI 316, some parts nickel plated (surcharge)
..Max-...- CTS	Aluminium housing of ..Max quarter-turn actuator size S with offshore/ marine coating, resistant against corrosive and maritime atmosphere, some parts nickel plated (surcharge)
..Max-...- CTM	Aluminium housing of ..Max quarter-turn actuator size M with offshore/ marine coating, resistant against corrosive and maritime atmosphere, some parts nickel plated (surcharge)
..Box-.../ VA	Ex-e terminal-box, housing made of stainless-steel type AISI 316 L, some parts nickel plated (surcharge)
..Box-.../ CT	Ex-e terminal-box, housing offshore/ marine coated, resistant against corrosive/ maritime atmosphere, some parts nickel plated (surcharge)
..Switch- CT	Auxiliary switch for ..Max-..., housing offshore/ marine coated, resistant against corrosive/ maritime atmosphere, some parts nickel plated (surcharge)
MKK- S/VA	Mounting bracket, made of stainless-steel suitable for ..Box-...VA for direct coupling to ..Max actuators size S
MKK- M/VA	Mounting bracket, made of stainless-steel suitable for ..Box-...VA for direct coupling to ..Max actuators size M
Kit-S8-Max	Cable glands 2 " M16 " 1,5 mm Ex-e standard Ø5-10 mm in brass nickel plated, 1 blind plug for replace the plastic version of quarter-turn actuator ..Max
Kit-S8-Box	Cable glands 2 " M20 " 1,5 mm Ex-e Ø6-13 mm, brass nickel plated, for replace the plastic version of terminal ..Box
Kit-Offs-PMC-1C	Protection metal conduit ind. SS terminal box and glands for 1 armoured cable
Kit-Offs-PMC-2C	Protection metal conduit ind. SS terminal box and glands for 2 armoured cables
WS-S	Weathershield in stainless steel, suitable for all ..Max actuators size S
WS-M	Weathershield in stainless steel, suitable for all ..Max actuators size M

..Run Special Options for Valve Actuators

Explosionproof		Features ..Run-...CTS	
..Run-...CTS	Special options	Description	Basics
available for ExRun, RedRun and InRun In accordance with type for use in Ex area or safe area		CTS version with aluminium housing and offshore/ marine coating, resistant against corrosive and maritime atmosphere, some parts nickel plated. Delivery: 1 valve actuator with special option Ordering example: ExRun-25.50-CTS	CTS: - offshore/ marine coated aluminium housing, resistant against corrosive and/ or maritime atmosphere - Cable glands brass nickel plated - Screws in stainless steel For general basics see ..Run valve actuators.

..Run-.. options

Type	Description/Technical data
..Run-...-CTS	Aluminium housing with offshore/ marine coating for ..Run valve actuator, resistant against corrosive/ maritime atmosphere, some parts nickel plated (surcharge)
Kit-S8-Run	Cable glands 2 " M20 " 1,5 mm Ex-e Ø6-13 mm, brass nickel plated, for replace the plastic version of valve actuators ..Run
Kit-Offs-GL-Run	Cable glands 2 " M25 " 1,5 mm Ex-d in brass nickel plated for armoured cables suitable for ..Run valve actuators
WS-R	Weathershield in stainless steel, suitable for all ..Run valve actuators

ExPolar/InPolar Heating System – Overview


Overview of new heating system for use with Schischek actuators down to ! 50°C

Application area:

Usage in hazardous locations for temperatures down to ! 50 °C.

Advantages:

- Especially for usage under high sub-zero temperatures down to ! 50°C
- Usage directly in hazardous locations (only ExPolar)
- Adaptable on our actuator series type..Max size S or M



ExPolar/InPolar Heating System for Quarter-Turn Actuators ..Max-.. Size S

Explosionproof	Industrial	Features ..Polar-...-MS	
ExPolar-...-MS Hazardous Location 	InPolar-...-MS Safe Area 	Description Controlled heating system for use in sub-zero regions down to ! 50 °C. Adaptable on our quarter-turn actuators ..Max-.. size S (depending on type). Delivery: 1 heating system (adaptable) Ordering example: ExPolar-240-MS	Basics • 24/48 VAC/DC, 120/240 VAC • 60 W • ! 50 °C... +60 °C • ExPolar for zone 1, 2, 21, 22 • InPolar for safe area

ExPolar-...-MS/InPolar-...-MS

Type	Adaptable on	Operation temperature	Supply	Power*	Installation area
ExPolar-...-MS	ExMax-../RedMax size S	!50 °C upto +60 °C	24 VAC/DC 48 VAC/DC 120 VAC 240 VAC	60 W	zone 1, 2, 21, 22
InPolar-...-MS	InMax-.. size S	!50 °C upto +60 °C	24 VAC/DC 48 VAC/DC 120 VAC 240 VAC	60 W	safe area

↑ Supply voltage
Not suitable for VA versions!

*Nominal value

ExPolar/InPolar Heating System for Quarter-Turn Actuators ..Max-.. Size M

Explosionproof	Industrial	Features ..Polar-...-MM	
ExPolar-...-MM Hazardous Location 	InPolar-...-MM Safe Area 	Description Controlled heating system for use in sub-zero regions down to ! 50 °C. Adaptable on our quarter-turn actuators ..Max-.. size M (depending on type). Delivery: 1 heating system (adaptable) Ordering example: ExPolar-240-MM	Basics • 24/48 VAC/DC, 120/240 VAC • 60 W • ! 50 °C... +60 °C • ExPolar for zone 1, 2, 21, 22 • InPolar for safe area

ExPolar-...-MM/InPolar-...-MM

Type	Adaptable on	Operation temperature	Supply	Power*	Installation area
ExPolar-...-MM	ExMax-../RedMax size M	!50 °C upto +60 °C	24 VAC/DC 48 VAC/DC 120 VAC 240 VAC	60 W	zone 1, 2, 21, 22
InPolar-...-MM	InMax-.. size M	!50 °C upto +60 °C	24 VAC/DC 48 VAC/DC 120 VAC 240 VAC	60 W	safe area


↑ Supply voltage
Not suitable for VA versions!

*Nominal value

Special option

Type	Description/Technical data
...Polar-...-CT	Housing offshore/marine coated, resistant against corrosive/maritime atmosphere, some parts nickel plated (surcharge)

ExArctic/InArctic Heating System for Actuators ..Max/..Run/..Max+LIN

Explosionproof	Industrial	Features ..Arctic-..	
ExArctic-M ExArctic-R Hazardous Location 	InArctic-M InArctic-R Safe Area 	Description Controlled heating system with protective housing for use down to ! 60 °C. Suitable for our actuators ..Max size S and M as well as for valve actuators ..Run / ..Max + LIN. Delivery: 1 heating system 1 protective housing 1 mounting material set	Basics • ! 60 °C • ExArctic for hazardous locations • InArctic for safe area • details and prices on request • subject to change



Overview of ExReg-.. and InReg-.. control technology

Installation areas:


ExReg-..... Modules for use in hazardous locations zone 1, 2, 21, 22
InReg-..... Modules for safe area

Application areas:

ExReg/InReg-V Modules for volume flow control (CAV/VAV)
ExReg/InReg-P Modules for differential pressure control (ΔP)

The new control systems concept offers especially in Ex-area huge benefits:


1. Usage directly in hazardous locations in zone 1, 2, 21, 22
2. Can be configured on site in the hazardous location
3. Decentralised control structures
4. Fewer components
5. Reduced Life-Cycle-Costs
6. No necessity to install safety barriers or to use special wiring
7. Integral PID loop
8. Optional in stainless steel (AISI 316) or with offshore/marine coating
9. Predefined Settings and damper characteristics
10. Cost effective



ExReg-V-.., InReg-V-..

Control of air flows and pressure in ventilation systems for building management control equipment, for chemical, pharmaceutical, industrial and offshore plants directly in hazardous locations zones 1, 2 (gas) and 21, 22 (dust), (InReg-V-.. in safe area). To complete the technical solution on a ventilation damper (with orifice plate and known shield/k-factor) an additional actuator type ExMax-...-CY or ExMax-...-CYF (with fail safe spring-return) is required.

VAV applications in a typical HVAC system



ExReg-V../InReg-V.. Volume Flow and Pressure Controller CAV/VAV

Explosionproof	Industrial	Features of ExReg-V.., InReg-V..	
ExReg-V.. Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, CCC, EAC	InReg-V.. NOT explosionproof and only for use in safe area IP66	Description Compact controller for use in hazardous areas zone 1, 2, 21, 22 or in safe area (depending on type) for control/regulation of air/gas flows and pressure in ventilation systems. VAV control must be tested by the manufacturer of VAV dampers in acc. with diameter, design and characteristics of the air damper! Suitable actuator ..Max-...-CY or ..Max-...-CYF available separately. Delivery: Electric volume flow/pressure controller with integrated terminal box (ExReg.. with "Ex-e"), 3 tapping screws, short circuit tube	Basics • No additional module in the panel required • No intrinsically safe wiring required • Adjustable "k-factor" • Measurement range 0...100/300/1.000 Pa • 24 VAC/DC • Switch-on delay 3 seconds • Air volume monitoring • PID controller • Programmable w/o additional tools • Alarm with alarm delay function • LCD backlight (which can be switched off) • Aluminium housing, protection IP66 • Integrated terminal box (ExReg.. with "Ex-e") • Optional offshore/marine coated or stainless steel edition • H" W" D= 180 " 107 " 66 mm

ExReg-V.. Volume flow and pressure controller for zone 1, 2, 21, 22

Type	Sensor	Supply	Meas. range	Connection/Interface (analogue)	Installation
ExReg-V100-A	Differential pressure	24 VAC/DC	0...100 Pa	1 " actuator, 1 " set point, 1 " actual value, 1 " position actuator	zone 1, 2, 21, 22
ExReg-V300-A	Differential pressure	24 VAC/DC	0...300 Pa	1 " actuator, 1 " set point, 1 " actual value, 1 " position actuator	zone 1, 2, 21, 22
ExReg-V1000-A	Differential pressure	24 VAC/DC	0...1.000 Pa	1 " actuator, 1 " set point, 1 " actual value, 1 " position actuator	zone 1, 2, 21, 22

InReg-V.. Volume flow and pressure controller for safe area

Type	Sensor	Supply	Meas. range	Connection/Interface (analogue)	Installation
InReg-V100-A	Differential pressure	24 VAC/DC	0...100 Pa	1 " actuator, 1 " set point, 1 " actual value, 1 " position actuator	safe area
InReg-V300-A	Differential pressure	24 VAC/DC	0...300 Pa	1 " actuator, 1 " set point, 1 " actual value, 1 " position actuator	safe area
InReg-V1000-A	Differential pressure	24 VAC/DC	0...1.000 Pa	1 " actuator, 1 " set point, 1 " actual value, 1 " position actuator	safe area

Actuators for ..Reg.. controller

Type	Torque	Running time 90°	Spring-return	Control mode	Feedback	Features	Size
ExMax- 5.10-CY	5 Nm/ 10 Nm	7,5/15/30/60/120 sec.	-	4...20 mA	0...10 V	combination with ExReg..	S
ExMax-15.30-CY	15 Nm/ 30 Nm	7,5/15/30/60/120 sec.	-	4...20 mA	0...10 V	combination with ExReg..	S
ExMax- 5.10-CYF	5 Nm/ 10 Nm	7,5/15/30/60/120 sec.	~ 10 sec.	4...20 mA	0...10 V	combination with ExReg..	S
ExMax-15- CYF	15 Nm	7,5/15/30/60/120 sec.	~ 10 sec.	4...20 mA	0...10 V	combination with ExReg..	S
InMax- 5.10-CY	5 Nm/ 10 Nm	7,5/15/30/60/120 sec.	-	4...20 mA	0...10 V	combination with InReg..	S
InMax- 15.30-CY	15 Nm/ 30 Nm	7,5/15/30/60/120 sec.	-	4...20 mA	0...10 V	combination with InReg..	S
InMax- 5.10-CYF	5 Nm/ 10 Nm	7,5/15/30/60/120 sec.	~ 10 sec.	4...20 mA	0...10 V	combination with InReg..	S
InMax- 15- CYF	15 Nm	7,5/15/30/60/120 sec.	~ 10 sec.	4...20 mA	0...10 V	combination with InReg..	S

Accessories

Type	Description/Technical data
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)
Kit 2	Includes 2 meter pressure hose (inner diameter 6 mm) and 2 plastic fittings

Special options and offshore kits see page 47



Overview of the ExCos-.., RedCos-.. and InCos-.. sensor technology

Installation areas:


ExCos-.....Sensors for use in hazardous locations zone 1, 2, 21, 22
 RedCos-.....Sensors for use in hazardous locations zone 2, 22
 InCos-.....Sensors for safe area

Application areas:

Ex/Red/InCos-P.....Sensors for pressure and differential pressure
 Ex/Red/InCos-D + ..Pro-C.....Sensors (active) for temperature and/or humidity
 EXL-IM-9282-.. (Ex-i) + ExSens.....Sensors (passive) for temperature, humidity and potentiometer

The sensor concept offers especially in Ex-area huge benefits:

1. No intrinsically safe wiring required between the control panel and the sensor
2. No intrinsically safe circuit necessary inside the control panel
3. No transmitter needed in the electrical control panel
4. Reduced installation cost
5. Easy installation
6. Easy parameterisation
7. Cost savings for electrical components
8. Actual value indication
9. Optional in stainless steel (AISI 316) or with offshore/marine coating



ExCos-P/RedCos-P/InCos-P Differential Pressure Transmitter

Explosionproof		Industrial	Features of ExCos-P..., RedCos-P..., InCos-P...	
ExCos-P-..	RedCos-P-..	InCos-P-..	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC, KOSHA	Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC	NOT Explosionproof and only for use in safe area IP66	ExCos-P..., RedCos-P... and InCos-P... are pressure transmitter for HVAC systems, e.g. for differential pressure control. Delivery: 1 sensor with integrated terminal box, 3 tapping screws, short circuit tube	- No additional module in the panel required! - No intrinsically safe wiring required! 24 VAC/DC supply - Outputs 0...10V, (0)4...20 mA selectable - Measurement range adjustable - Actual value indication (which can be switched off) - All parameters can be adjusted on site without additional tools and measurement devices - Aluminium housing IP66 - Integrated terminal box (ExCos... with "Ex-e") - Dimensions (H" W" D) 180" 107" 66 mm
				

ExCos-P... Differential pressure and volume control transmitter for zone 1, 2, 21, 22

Type	Max. range	Overload protected	Measurement range, min. 20% of max. range	Installation module
ExCos-P- 100	± 100 Pa	up to 25.000 Pa	± Measurement range free adjustable, min. range 20 Pa	zone 1, 2, 21, 22
ExCos-P- 250	± 250 Pa	up to 25.000 Pa	± Measurement range free adjustable, min. range 50 Pa	zone 1, 2, 21, 22
ExCos-P- 500	± 500 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 100 Pa	zone 1, 2, 21, 22
ExCos-P-1250	± 1.250 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 250 Pa	zone 1, 2, 21, 22
ExCos-P-2500	± 2.500 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 500 Pa	zone 1, 2, 21, 22
ExCos-P-5000	± 5.000 Pa	up to 75.000 Pa	± Measurement range free adjustable, min. range 1.000 Pa	zone 1, 2, 21, 22
ExCos-P-7500	± 7.500 Pa	up to 120.000 Pa	± Measurement range free adjustable, min. range 1.500 Pa	zone 1, 2, 21, 22

RedCos-P... Differential pressure and volume control transmitter for zone 2, 22

Type	Max. range	Overload protected	Measurement range, min. 20% of max. range	Installation module
RedCos-P- 100	± 100 Pa	up to 25.000 Pa	± Measurement range free adjustable, min. range 20 Pa	zone 2, 22
RedCos-P- 250	± 250 Pa	up to 25.000 Pa	± Measurement range free adjustable, min. range 50 Pa	zone 2, 22
RedCos-P- 500	± 500 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 100 Pa	zone 2, 22
RedCos-P-1250	± 1.250 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 250 Pa	zone 2, 22
RedCos-P-2500	± 2.500 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 500 Pa	zone 2, 22
RedCos-P-5000	± 5.000 Pa	up to 75.000 Pa	± Measurement range free adjustable, min. range 1.000 Pa	zone 2, 22
RedCos-P-7500	± 7.500 Pa	up to 120.000 Pa	± Measurement range free adjustable, min. range 1.500 Pa	zone 2, 22

InCos-P... Differential pressure and volume control transmitter for safe area

Type	Max. range	Overload protected	Measurement range, min. 20% of max. range	Installation module
InCos-P- 100	± 100 Pa	up to 25.000 Pa	± Measurement range free adjustable, min. range 20 Pa	safe area
InCos-P- 250	± 250 Pa	up to 25.000 Pa	± Measurement range free adjustable, min. range 50 Pa	safe area
InCos-P- 500	± 500 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 100 Pa	safe area
InCos-P-1250	± 1.250 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 250 Pa	safe area
InCos-P-2500	± 2.500 Pa	up to 50.000 Pa	± Measurement range free adjustable, min. range 500 Pa	safe area
InCos-P-5000	± 5.000 Pa	up to 75.000 Pa	± Measurement range free adjustable, min. range 1.000 Pa	safe area
InCos-P-7500	± 7.500 Pa	up to 120.000 Pa	± Measurement range free adjustable, min. range 1.500 Pa	safe area

Accessories and special designs

Type	Description/Technical data
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)
Kit 2	Includes 2 meter pressure hose (inner diameter 6 mm) and 2 plastic fittings

Special options and offshore kits see page 47

ExCos-D/RedCos-D/InCos-D Temperature/Humidity Transmitter

Explosionproof		Industrial	Features ExCos-D, RedCos-D, InCos-D	
ExCos-D	RedCos-D	InCos-D	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC, KOSHA	Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC	NOTE: Explosionproof and only for use in safe area IP66	ExCos-D, RedCos-D and InCos-D transmitter together with ExPro-C.../InPro-C... sensors are for temperature and/or humidity measurement in HVAC systems. Delivery: 1 transmitter with connection for 1 ExPro-C... sensor, 3 tapping screws Required accessory (additional price): 1 ExPro-C... or InPro-C... sensor Ordering example for temperature duct sensing in hazardous location in zone 21, 150 mm sensor tube. Types to order: 1 " ExCos-D 1 " ExPro-CT-150	- No additional module in the panel required! - No intrinsically safe wiring required! 24 VAC/DC supply - Connector for ExPro-C... sensors for room or duct mounting - Outputs 0...10V, 4...20 mA selectable - Measurement range adjustable - Actual value indication (which can be switched off) - All parameters can be adjusted on site without additional tools and measurement devices - Aluminium housing IP66 - Integrated terminal box (ExCos.. with "Ex-e") - Dimensions (H" W" D) 180" 107" 66 mm
				

ExCos-D temperature-/humidity module for zone 1, 2, 21, 22

Type	Description/Technical data	Installation module	Installation ExPro sensor
ExCos-D	Module to connect 1 ExPro-C... sensor for temperature and/or humidity for use in hazardous locations	zone 1, 2, 21, 22	zone 1, 2, 21, 22

RedCos-D temperature-/humidity module for zone 2, 22

Type	Description/Technical data	Installation module	Installation ExPro sensor
RedCos-D	Module to connect 1 ExPro-C... sensor for temperature and/or humidity for use in hazardous locations	zone 2, 22	zone 1, 2, 21, 22

InCos-D temperature-/humidity module for safe area


Type	Description/Technical data	Installation module	Installation InPro sensor
InCos-D	Module to connect 1 InPro-C... sensor for temperature and/or humidity for use in safe area	safe area	safe area

Accessories and special designs

Type	Description/Technical data
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)
VL3	Sensor extension cable 3 m

Special options and offshore kits see page 47

Example of combinations



ExPro-C../InPro-C.. Temperature/Humidity Sensors

Explosionproof	Industrial	Features ExPro-C..., InPro-C..	
ExPro-C.. Zone 1, 2, 21, 22 Gas+ Dust Etype-approved with ExCos-D/RedCos-D transmitter	InPro-C.. Only for use with InCos-D...transmitter! NOT for use in Ex area!	Description ExPro-C.. sensors are used for measurements of temperature and/or humidity in hazardous locations, for exclusive use with ExCos-D/RedCos-D transmitter! InPro-C.. sensors are suitable for temperature and/or humidity measurements in safe areas, for exclusive use with InCos-D transmitter! Delivery: 1 sensor with connector Example: room-humidity sensor, 50 mm length Type: 1 x ExPro-CF-50 Attention: only in combination with: 1 " ExCos-D or RedCos-D transmitter (InCos-D by InPro-C.. sensors)	Basics - ExPro-C.. Sensors for connection to ExCos-D or RedCos-D transmitter (InPro-C.. sensors for InCos-D transmitter) - Mechanical and electrical adaptation via connector - ExPro-C../InPro-C.. sensors can be screwed to the housing optionally at the back (duct measurement) or bottom (room measurement) - When using humidity-sensors, the contamination and aggressiveness of the medium has to be regarded
			

Sensors for ExCos-D and RedCos-D transmitter

Type	Function	Range	Sensor length	Main use	Connectable to		Installation area
ExPro-CT - 50	Temperature sensor	!40...+ 80 °C	50 mm	Room/Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CT -100	Temperature sensor	!40...+ 125 °C	100 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CT -150	Temperature sensor	!40...+ 125 °C	150 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CT -200	Temperature sensor	!40...+ 125 °C	200 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CF - 50	Humidity sensor	0...100 %rF	50 mm	Room/Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CF -100	Humidity sensor	0...100 %rF	100 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CF -150	Humidity sensor	0...100 %rF	150 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CF -200	Humidity sensor	0...100 %rF	200 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CTF- 50	Combination temperature/humidity	!40...+ 80 °C, 0...100 %rH	50 mm	Room/Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CTF-100	Combination temperature/humidity	!40...+ 125 °C, 0...100 %rH	100 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CTF-150	Combination temperature/humidity	!40...+ 125 °C, 0...100 %rH	150 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22
ExPro-CTF-200	Combination temperature/humidity	!40...+ 125 °C, 0...100 %rH	200 mm	Duct	ExCos-D	RedCos-D	zone 1, 2, 21, 22

Sensors for InCos-D transmitter

Type	Function	Range	Sensor length	Main use	Connectable to		Installation area
InPro-CT - 50	Temperature sensor	!40...+ 80 °C	50 mm	Room/Duct	InCos-D		safe area
InPro-CT -100	Temperature sensor	!40...+ 125 °C	100 mm	Duct	InCos-D		safe area
InPro-CT -150	Temperature sensor	!40...+ 125 °C	150 mm	Duct	InCos-D		safe area
InPro-CT -200	Temperature sensor	!40...+ 125 °C	200 mm	Duct	InCos-D		safe area
InPro-CF - 50	Humidity sensor	0...100 %rF	50 mm	Room/Duct	InCos-D		safe area
InPro-CF -100	Humidity sensor	0...100 %rF	100 mm	Duct	InCos-D		safe area
InPro-CF -150	Humidity sensor	0...100 %rF	150 mm	Duct	InCos-D		safe area
InPro-CF -200	Humidity sensor	0...100 %rF	200 mm	Duct	InCos-D		safe area
InPro-CTF- 50	Combination temperature/humidity	!40...+ 80 °C, 0...100 %rH	50 mm	Room/Duct	InCos-D		safe area
InPro-CTF-100	Combination temperature/humidity	!40...+ 125 °C, 0...100 %rH	100 mm	Duct	InCos-D		safe area
InPro-CTF-150	Combination temperature/humidity	!40...+ 125 °C, 0...100 %rH	150 mm	Duct	InCos-D		safe area
InPro-CTF-200	Combination temperature/humidity	!40...+ 125 °C, 0...100 %rH	200 mm	Duct	InCos-D		safe area

Accessories

Type	Description/Technical data
MFK	Mounting flange for duct-installation, for variable depth of immersion in the air duct
TH- VA	Probe made of stainless-steel V4A 1.4571, length 150 mm for ..Pro-CT-200. Other lengths on request
Kit-FA-VA	Sinter filter cap for humidity sensor (only up to 90 %rH)
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)

ExLine Ex-transmitter with Ex-i Circuit for Zone 0, 1, 2, 20, 21, 22

Explosionproof		Features EXL-IM-9282-12-51-16s C2305 TMU	
EXL-IM-9282-..	EXL-IM-9282-..	Description	Basics
Zone 0, 1, 2, 20, 21, 22 Gas + Dust certified according to ATEX, IECEx, CSA, FMUL, EAC, INMETRO, KOSHA, PESO		Module with intrinsically safe circuit to change a passive sensor signal (e.g. PT100) into an active mAV signal. Module must be installed in the safe area, sensor in the hazardous location! Delivery: 1 Ex-i module for DIN rail mounting Accessory (optional): analog sensor type ExSens	• 24 V DC power supply • Inverse-polarity protection • Transmitter for passive, potential free, analog sensors series ExSens, 2-3-4-wire connection • Simple configuration via software or DIP-switches • Input: PT100, PT500, PT1000, Ni100, Ni500, Ni1000, 0...1.000 Ohm • Output: 4...20 mA, with additional plug 0...10V • LED operation indication • Dimensions (W" H" D) 17,6" 99" 114,5mm • Rail mounting according to DIN, installation in safe area

EXL-IM-9282-12-51-16s C2305 TMU transmitter

Type	Description/Technical data	Installation module	Installation sensor*
EXL-IM-9282-..	1 module (rail mounting) for 1 passive sensor series ExSens	safe area	zone 0, 1, 2, 20, 21, 22
Optional:			
Plug 0-10V-9182	for output 0...10V (installation in safe area)		
N1 supply unit	Input 120...240 VAC, output 24 VDC, max. 0,5 A, max. 4 pcs. EXL-IM... connectable. N1 supply unit is required only in case of 120...240 VAC supply!		

*in acc. with certification of sensor!

ExSens Passive Analog Sensors for Zone 1, 2, 21, 22

Explosionproof		Features analog ExSens sensors	
ExSens	passive	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX Manufacturer certificate		ExSens sensors for temperature, humidity or pressure measurement in hazardous locations with manufacturer certification in acc. with ATEX directives. These sensors are passive and potential free. Delivery: 1 Sensor Ordering example for 1 room humidity sensor Type to purchase: 1" FFR-2G	• Sensors for installation in hazardous locations, connected to a relevant transmitter, for e.g. EXL-IM-9282-... • The transmitter changes the passive resistance signal into an active 4...20 mA signal (with additional plug 0...10V) • Sensor is installed in the hazardous location, module in the safe area

Sensors, connectable to transmitter EXL-IM-9282-...

Type	Function	Measuring range	Sensor	Connectable to transmitter	Sensor in zone
TFR -2G	Room temperature	!30...+ 60 °C	Pt 100 DIN	EXL-IM-9282-...	1, 2
TFR -2G3D	Room temperature (IP65)	!40...+ 60 °C	Pt 100 DIN	EXL-IM-9282-...	1, 2, 22
TFK -2G3D	Duct temperature (IP65), 200 mm	!30...+150 °C	Pt 100 DIN	EXL-IM-9282-...	1, 2, 22
TFK -2G3D-400	Duct temperature, length 400 mm	!30...+150 °C	Pt 100 DIN	EXL-IM-9282-...	1, 2, 22
TFT -2G3D	Sensor temperature (IP65), 100 mm	!30...+150 °C	Pt 100 DIN, tubing G1/2" Ms	EXL-IM-9282-...	1, 2, 22
TFT-V4A-2G3D	Sensor temperature (IP65), 100 mm	!30...+150 °C	Pt 100 DIN, tubing G1/2" VA	EXL-IM-9282-...	1, 2, 22
TFM -2G-3	Mean value temperature 3 m	!20...+ 70 °C	Pt 100 DIN	EXL-IM-9282-...	1, 2
TFR-AN -2G3D	Room temperature direct contact	!30...+110 °C	Pt 100 DIN	EXL-IM-9282-...	1, 2, 22
FFR -2G	Room humidity	30...100 %rF	0...1 kΩ	EXL-IM-9282-...	1, 2
FFK -2G	Duct humidity	30...100 %rF	0...1 kΩ	EXL-IM-9282-...	1, 2
TFFR -2G	Room combination temp/humidity	30...100 %rF, -10...+60 °C	0...1 kΩ, Pt 100	2" EXL-IM-9282-...	1, 2
TFFK -2G	Duct combination temp/humidity	30...100 %rF, -20...+60 °C	0...1 kΩ, Pt 100	2" EXL-IM-9282-...	1, 2
TFH -2G	Temperature sensors in ventilation and ducts	!50...+ 80 °C	PT100/PT1000	EXL-IM-9282-...	1, 2

Applications for differential pressure, temperature, humidity, fan belt monitoring and frost protection ...



- › Hazardous locations zone 1, 2, 21, 22
- › No module in panel needed
- › No intrinsic safe circuits needed
- › Easy installation
- › Easy parameterisation
- › Reduced installation cost
- › Offshore/marine coated version
- › Stainless steel solution
- › Actual value indication

Overview of the ExBin-.., RedBin-.. and InBin-.. sensor technology

Installation areas:



ExBin-..... Sensors for use in hazardous locations zone 1, 2, 21, 22
 RedBin-..... Sensors for use in hazardous locations zone 2, 22
 InBin-..... Sensors for safe area

Application areas:

Ex/Red/InBin-P..... Sensors for pressure and differential pressure monitoring
 Ex/Red/InBin-FR..... Sensors for frost protection monitoring
 Ex/Red/InBin-D + ..Pro-B..... Sensors (active) for temperature and/or humidity monitoring
 Ex/Red/InBin-A + ExSens..... Sensors (passive) for temperature, humidity, pressure monitoring
 EXL-IR-9270-.. (Ex-i) + ExSens..... Sensors (passive) for temperature, humidity, pressure, filter and fan monitoring

The binary sensor concept offers especially in Ex-area huge benefits:

1. No intrinsically safe wiring required between the control panel and the sensor
2. No intrinsically safe circuit necessary inside the control panel
3. No switching module needed in the electrical control panel
4. Reduced installation cost
5. Easy installation
6. Easy parameterisation
7. 1- and 2-stage versions available
8. Actual value indication
9. Optional in stainless steel (AISI 316) or with offshore/marine coating

"P"	ExBin-P 	Pressure, differential pressure (Filter/fan belt monitoring) – active	 normal wiring	ExBin-P-.., RedBin-P-.., InBin-P-.. Binary pressure/differential pressure auxiliary switch 0...5.000 Pa, for direct connection of air hoses. IP66 Aluminium die-cast housing with integrated terminal box. Set points adjustable on site, output 1 potential-free make contact. Integrated indication of actual value, illuminated. 2-stage version optionally available.
°C	ExBin-FR 	Frost protection thermostats – active	 normal wiring	ExBin-FR-.., RedBin-FR-.., InBin-FR-.. Frost protection thermostat mechanically adjustable and switching. Setting range !10...+15 °C. 3 or 6 m capillary as sensor with a resolution of 40 cm effective range. Switching status display with LED. IP66 Aluminium die-cast housing with integrated terminal box. Output 1 potential-free make contact.
°C %rH	ExBin-D + ExPro-B.. 	Thermostats, hygrometers – active	 normal wiring	ExBin-D, RedBin-D, InBin-D + ExPro-B.. respectively InPro-B.. Sensor Thermostats and/or hygrometers for connection of one ExPro-B.. respectively InPro-B.. sensor. Operating range adjustable. Indication of actual value. IP66 Aluminium die-cast housing with integrated terminal box. Output 1 potential-free make contact. 2-stage version optionally available.
°C %rH "P"	ExBin-A + ExSens 	1- or 2-channel switching module for passive sensors	 normal wiring Ex-i wiring (intrinsically safe)	ExBin-A1/A2, RedBin-A1/A2 + ExSens switching sensors 1- or 2-channel Ex-switching module for connection of max. 2 passive, potential-free switching sensors. Switching status display with LED. IP66 Aluminium die-cast housing with integrated terminal box. Output depending on type 1-2 make contacts with collective supply unit.
°C %rH "P"	EXL-IR-.. + ExSens 	Temperature, humidity, diff. pressure switching module for passive sensors	 normal wiring Ex-i wiring (intrinsically safe)	EXL-IR-.. switching module + ExSens sensor Ex-switching module for connection of one passive, switching ExSens sensor, such as differential pressure switch, frost protection thermostat or hygrometer through intrinsically safe electrical conduit. Installation in control box onto DIN-rail. Output is potential-free.
			Safe area Ex area	

ExBin-P/RedBin-P/InBin-P Pressure/Differential Pressure Switch, Binary

Explosionproof		Industrial	Features of ExBin-P-.., RedBin-P-.., InBin-P-..	
ExBin-P-..	RedBin-P-..	InBin-P-..	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC, KOSHA, CCC	Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC	NOT Explosionproof and only for use in safe area IP66	ExBin-P-.., RedBin-P-.. and InBin-P-.. are pressure switches for HVAC systems, e.g. for differential pressure control for filter- or fan belt monitoring. ..Bin-P-100 pressure switch allows an achievement of new applications with a smaller differential pressure range. Additionally the ..Bin-P-100 has an adjustable switch activation delay contact for applications which require a time-delayed fault indication, for example short opening of doors in clean room environment. Delivery: 1 Pressure switch with integrated terminal box, 3 tapping screws	- No additional module in the panel required! - No intrinsically safe wiring required! 24 VAC/DC supply 1-channel: 1 potential-free contact 2-channel (optional): 2 potential-free contacts - Switch-point is digitally adjustable - Indication of actual value (can be switched off) - Switching status display over LED - All parameters can be adjusted on site without additional tools and measurement devices - Aluminium housing IP66 - Integrated terminal box (ExBin-.. with "Ex-e") ..Bin-P-100 with switch activation delay, adjustable from 0...240 s - Dimensions (H" W" D) 180" 107" 66 mm
				

ExBin-P-.. Differential pressure switch for zone 1, 2, 21, 22

Type	Measurement range	Safe overload	Setting range	Special feature	Installation module
ExBin-P- 100	0... 100 Pa	up to 5.000 Pa	1-stage adjustable switch-point in meas. range	adjustable switch activation delay 0...240 s	zone 1, 2, 21, 22
ExBin-P- 500	0... 500 Pa	up to 5.000 Pa	1-stage adjustable switch-point in meas. range		zone 1, 2, 21, 22
ExBin-P- 500-2	0... 500 Pa	up to 5.000 Pa	2-stage adjustable switch-point in meas. range		zone 1, 2, 21, 22
ExBin-P-5000	0...5.000 Pa	up to 50.000 Pa	1-stage adjustable switch-point in meas. range		zone 1, 2, 21, 22
ExBin-P-5000-2	0...5.000 Pa	up to 50.000 Pa	2-stage adjustable switch-point in meas. range		zone 1, 2, 21, 22

RedBin-P-.. Differential pressure switch for zone 2, 22

Type	Measurement range	Safe overload	Setting range	Special feature	Installation module
RedBin-P- 100	0... 100 Pa	up to 5.000 Pa	1-stage adjustable switch-point in meas. range	adjustable switch activation delay 0...240 s	zone 2, 22
RedBin-P- 500	0... 500 Pa	up to 5.000 Pa	1-stage adjustable switch-point in meas. range		zone 2, 22
RedBin-P- 500-2	0... 500 Pa	up to 5.000 Pa	2-stage adjustable switch-point in meas. range		zone 2, 22
RedBin-P-5000	0...5.000 Pa	up to 50.000 Pa	1-stage adjustable switch-point in meas. range		zone 2, 22
RedBin-P-5000-2	0...5.000 Pa	up to 50.000 Pa	2-stage adjustable switch-point in meas. range		zone 2, 22


InBin-P-.. Differential pressure switch for safe area

Type	Measurement range	Safe overload	Setting range	Special feature	Installation module
InBin-P- 100	0... 100 Pa	up to 5.000 Pa	1-stage adjustable switch-point in meas. range	adjustable switch activation delay 0...240 s	safe area
InBin-P- 500	0... 500 Pa	up to 5.000 Pa	1-stage adjustable switch-point in meas. range		safe area
InBin-P- 500-2	0... 500 Pa	up to 5.000 Pa	2-stage adjustable switch-point in meas. range		safe area
InBin-P-5000	0...5.000 Pa	up to 50.000 Pa	1-stage adjustable switch-point in meas. range		safe area
InBin-P-5000-2	0...5.000 Pa	up to 50.000 Pa	2-stage adjustable switch-point in meas. range		safe area

Accessories

Type	Description/Technical data
Kit 2	Includes 2 meter pressure hose (inner diameter 6 mm) and 2 plastic fittings
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)

Special options and offshore kits see page 47



ExBin-FR/RedBin-FR/InBin-FR Frost Protection Thermostats

Explosionproof		Industrial	Features ExBin-FR-.., RedBin-FR-.., InBin-FR-..	
ExBin-FR-..	RedBin-FR-..	InBin-FR-..	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC	Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC	NOTE: Explosionproof and only for use in safe area IP66	ExBin-FR-.., RedBin-FR-.. and InBin-FR-.. are frost protection thermostats for HVAC systems, e.g. for frost protection monitoring of heating registers/heat exchangers. Delivery: 1 Frost protection thermostat with integrated terminal box, with 3 m or 6 m capillary (depending on type), 3 tapping screws Recommended accessory: for ..Bin-FR-3: Kit 1.3 for ..Bin-FR-6: Kit 1.6	- No additional module in the panel required! - No intrinsically safe wiring required! 24 VAC/DC supply - Temperature sensing by capillary with 3 m or 6 m length (depending on type) - Min. reaction length of capillary ~ 40 cm 1 potential-free contact - Switch-point is adjustable mechanically - Switching status display with LED - Aluminium housing IP66 - Integrated terminal box (ExBin-.. with "Ex-e") - Dimensions (H" W" D) 180 " 107 " 66 mm
				

ExBin-FR-.. frost protection thermostats for zone 1, 2, 21, 22

Type	Capillary	Temperature range	Setting range	Installation module
ExBin-FR-3	3 m	!10 ... +15 °C	1-stage adjustable switch-point in temperature range	zone 1, 2, 21, 22
ExBin-FR-6	6 m	!10 ... +15 °C	1-stage adjustable switch-point in temperature range	zone 1, 2, 21, 22

RedBin-FR-.. frost protection thermostats for zone 2, 22

Type	Capillary	Temperature range	Setting range	Installation module
RedBin-FR-3	3 m	!10 ... +15 °C	1-stage adjustable switch-point in temperature range	zone 2, 22
RedBin-FR-6	6 m	!10 ... +15 °C	1-stage adjustable switch-point in temperature range	zone 2, 22


InBin-FR-.. frost protection thermostats for safe area

Type	Capillary	Temperature range	Setting range	Installation module
InBin-FR-3	3 m	!10 ... +15 °C	1-stage adjustable switch-point in temperature range	safe area
InBin-FR-6	6 m	!10 ... +15 °C	1-stage adjustable switch-point in temperature range	safe area

Accessories

Type	Description/Technical data
Kit 1.3	Capillary duct, assembly cramp and 4 assembly brackets for frost protection thermostat ..Bin-FR-3
Kit 1.6	Capillary duct, assembly cramp and 8 assembly brackets for frost protection thermostat ..Bin-FR-6
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)

Special options and offshore kits see page 47



ExBin-A/RedBin-A/InBin-A Switching Modules

Explosionproof		Industrial	Features of ExBin-A-.., RedBin-A-.., InBin-A-..	
ExBin-A-..	RedBin-A-..	InBin-A-..	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC	Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC	NOT Explosionproof and only for use in safe area IP66	ExBin-A-.., RedBin-A-.. and InBin-A-.. modules are switching modules for direct mounting in Ex areas (except InBin-A) with 1 or 2 channels, for connection of 1 or 2 passive, potential-free, switching sensors, for use in HVAC systems. Delivery: 1 module with sockets for 1 or 2 ExSens sensors (dependent on type), 3 tapping screws Accessory (optional): Binary sensors series ExSens, see next page	- No additional module in the panel required! - No intrinsically safe wiring required! - Mounting of module directly in Ex area 24 VAC/DC supply - Sockets for 1 or 2 passive, potential-free, switching sensors 1 or 2 contacts with common supply unit 1 or 2 contacts with additional clamp for time switch relay, e.g. for 2 fan belt monitoring applications (time 120 sec.) - Switching status display with LED - Aluminium housing IP66 - Integrated terminal box (ExBin-.. with "Ex-e") - Dimensions (H" W" D) 180" 107" 66 mm
				

ExBin-A-.. Switching modules for 1 or 2 passive switching sensors for zone 1, 2, 21, 22

Type	Description/Technical data	Installation module	Installation sensor*
ExBin-A-1	Module (1 channel) to connect 1 switching ExSens sensor in Ex area	zone 1, 2, 21, 22	zone 0, 1, 2, 20, 21, 22
ExBin-A-2	Module (2 channel) to connect 2 switching ExSens sensors in Ex area	zone 1, 2, 21, 22	zone 0, 1, 2, 20, 21, 22

*in acc. with certification of sensor!

RedBin-A-.. Switching modules for 1 or 2 passive switching sensors for zone 2, 22

Type	Description/Technical data	Installation module	Installation sensor*
RedBin-A-1	Module (1 channel) to connect 1 switching ExSens sensor in Ex area	zone 2, 22	zone 0, 1, 2, 20, 21, 22
RedBin-A-2	Module (2 channel) to connect 2 switching ExSens sensors in Ex area	zone 2, 22	zone 0, 1, 2, 20, 21, 22

*in acc. with certification of sensor!


InBin-A-.. Switching modules for 1 or 2 passive switching sensors for safe area

Type	Description/Technical data	Installation module	Installation sensor
InBin-A-1	Module (1 channel) to connect 1 switching sensor	safe area	safe area
InBin-A-2	Module (2 channel) to connect 2 switching sensors	safe area	safe area

Accessories

Type	Description/Technical data
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)

Special options and offshore kits see page 47



ExBin-D/RedBin-D/InBin-D Thermostats, Hygrostats

Explosionproof		Industrial	Features of ExBin-D-., RedBin-D-., InBin-D-..	
ExBin-D-..	RedBin-D-..	InBin-D-..	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC	Zone 2, 22 Gas + Dust certified according to ATEX, IECEx, EAC	NOT Explosionproof and only for use in safe area IP66	ExBin-D-., RedBin-D-.. and InBin-D-.. modules are used together with ExPro-B../InPro-B.. sensors as thermostats or hygrostats in HVAC systems. Delivery: 1 Ex/Red/InBin.. module with socket for 1 ExPro-B../InPro-B.. sensor, 3 tapping screws Required accessory (additional price): ExPro-B.. or InPro-B.. sensor Ordering example for one thermostat in an air duct, 150 mm sensor length, with sensor in Ex zone 21. Types to order: 1 " ExBin-D-.. 1 " ExPro-BT150(Ex-i sensor)	- No additional module in the panel required! - No intrinsically safe wiring required! 24 VAC/DC supply - Socket for ExPro-B.. sensor - Selectable on site if used for room or duct application - Switch-point for °C and %RH separately adjustable (dependent on sensor type) 1-channel: 2 pot.-free contacts (1 "°C, 1 "%RH) 2-channel: 4 pot.-free contacts (2 "°C, 2 "%RH) - Display with indication of actual value - Switching status display with LED - Aluminium housing IP66 - Integrated terminal box (ExBin-.. with "Ex-e") - Dimensions (H" W" D) 180 " 107 " 66 mm
				

ExBin-D-.. thermostats and/or hygrostats, dependent on sensor type ExPro-B.. for zone 1, 2, 21, 22

Type	Description/Technical data	Installation module	Installation ExPro-B.. sensor
ExBin-D	Module for connection of one ExPro-B.. sensor as thermostat and/or hygrostat, 1-stage	zone 1, 2, 21, 22	zone 1, 2, 21, 22
ExBin-D-2	Module for connection of one ExPro-B.. sensor as thermostat and/or hygrostat, 2-stage	zone 1, 2, 21, 22	zone 1, 2, 21, 22

RedBin-D-.. thermostats and/or hygrostats, dependent on sensor type ExPro-B.. for zone 2, 22

Type	Description/Technical data	Installation module	Installation ExPro-B.. sensor
RedBin-D	Module for connection of one ExPro-B.. sensor as thermostat and/or hygrostat, 1-stage	zone 2, 22	zone 1, 2, 21, 22
RedBin-D-2	Module for connection of one ExPro-B.. sensor as thermostat and/or hygrostat, 2-stage	zone 2, 22	zone 1, 2, 21, 22

InBin-D-.. thermostats and/or hygrostats, dependent on sensor type InPro-B.. for safe area


Type	Description/Technical data	Installation module	Installation InPro-B.. sensor
InBin-D	Module for connection of one InPro-B.. sensor as thermostat and/or hygrostat, 1-stage	safe area	safe area
InBin-D-2	Module for connection of one InPro-B.. sensor as thermostat and/or hygrostat, 2-stage	safe area	safe area

Accessories

Type	Description/Technical data
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)
VL3	Sensor extension cable 3 m

Special options and offshore kits see page 47

Example of combinations



ExPro-B.../InPro-B... Thermostat/Hygrostat Sensors

Explosionproof	Industrial	Features of ExPro-B..., InPro-B...	
ExPro-B... Zone 1, 2, 21, 22 Gas + Dust E type-approved with ExBin-D-/RedBin-D- modules 	InPro-B... Only for use with InBin-D... transmitter! NOT for use in Ex area! 	Description ExPro-B... sensors are used for measurements of temperature and/or humidity in hazardous locations, for exclusive use with ExBin-D.../RedBin-D... modules! InPro-B... sensors are suitable for temperature and/or humidity measurements in safe areas, for exclusive use with InBin-D... modules! Delivery: 1 sensor with connector Example: room-humidity sensor, 50 mm length Type: 1 " ExPro-BF-50 Attention: only in combination with: 1 " ExBin-D... or RedBin-D... (InBin-D... with InPro-B... sensors)	Basics - Sensors for connection to ExBin-D..., RedBin-D..., InBin-D... modules. Adaption via connector - ExPro-B.../InPro-B... sensors can be optionally screwed to the housing at the back (duct measurement) or bottom (room measurement) - When using humidity-sensors, the contamination and aggressiveness of the medium has to be regarded

Sensors for ExBin-D... and RedBin-D... modules

Type	Function	Measurement range	Sensor length	Main use	Connectable to		Installation area
ExPro-BT - 50	Thermostat	!40...+ 80 °C	50 mm	Room/Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BT -100	Thermostat	!40...+ 125 °C	100 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BT -150	Thermostat	!40...+ 125 °C	150 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BT -200	Thermostat	!40...+ 125 °C	200 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BF - 50	Hygostat	0...100 %rH	50 mm	Room/Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BF -100	Hygostat	0...100 %rH	100 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BF -150	Hygostat	0...100 %rH	150 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BF -200	Hygostat	0...100 %rH	200 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BTF- 50	Combination Thermostat/Hygrostat	!40...+ 80 °C, 0...100 %rH	50 mm	Room/Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BTF-100	Combination Thermostat/Hygrostat	!40...+ 125 °C, 0...100 %rH	100 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BTF-150	Combination Thermostat/Hygrostat	!40...+ 125 °C, 0...100 %rH	150 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22
ExPro-BTF-200	Combination Thermostat/Hygrostat	!40...+ 125 °C, 0...100 %rH	200 mm	Duct	ExBin-D	RedBin-D	zone 1, 2, 21, 22

Sensors for InBin-D... modules

Type	Function	Measurement range	Sensor length	Main use	Connectable to	Installation area
InPro-BT - 50	Thermostat	!40...+ 80 °C	50 mm	Room/Duct	InBin-D	safe area
InPro-BT -100	Thermostat	!40...+ 125 °C	100 mm	Duct	InBin-D	safe area
InPro-BT -150	Thermostat	!40...+ 125 °C	150 mm	Duct	InBin-D	safe area
InPro-BT -200	Thermostat	!40...+ 125 °C	200 mm	Duct	InBin-D	safe area
InPro-BF - 50	Hygostat	0...100 %rH	50 mm	Room/Duct	InBin-D	safe area
InPro-BF -100	Hygostat	0...100 %rH	100 mm	Duct	InBin-D	safe area
InPro-BF -150	Hygostat	0...100 %rH	150 mm	Duct	InBin-D	safe area
InPro-BF -200	Hygostat	0...100 %rH	200 mm	Duct	InBin-D	safe area
InPro-BTF- 50	Combination Thermostat/Hygrostat	!40...+ 80 °C, 0...100 %rH	50 mm	Room/Duct	InBin-D	safe area
InPro-BTF-100	Combination Thermostat/Hygrostat	!40...+ 125 °C, 0...100 %rH	100 mm	Duct	InBin-D	safe area
InPro-BTF-150	Combination Thermostat/Hygrostat	!40...+ 125 °C, 0...100 %rH	150 mm	Duct	InBin-D	safe area
InPro-BTF-200	Combination Thermostat/Hygrostat	!40...+ 125 °C, 0...100 %rH	200 mm	Duct	InBin-D	safe area

Accessories

Type	Description/Technical data
MPK	Mounting flange for duct-installation, for variable depth of immersion in the air duct
TH- VA	Probe made of stainless-steel V4A 1.4571, length 150 mm for ..Pro-BT-200. Other lengths on request
Kit-FA-VA	Sinter filter cap for humidity sensor (only up to 90 %rH)
MKR-VA/AL	Mounting bracket for installation on round air-ducts (diameter up to 600 mm)

ExLine Ex-switching Module for Potential Free, Binary Signals in Zone 0, 1, 2, 20, 21, 22

Explosionproof		Features EXL-IR-9270-11-16-14sC2304 SV	
EXL-IR-9270-..	EXL-IR-9270-..	Description	Basics
Zone 0, 1, 2, 20, 21, 22 Gas + Dust certified according to ATEX, IECEx, CSA, FMVUL, EAC, INMETRO, KOSHA		Module with intrinsically safe circuit to change a passive potential free binary signal (e.g. contact) into a contact in the safe area. Module must be installed in the safe area, sensor in the hazardous location! Delivery: 1 Ex-i module for DIN rail mounting Accessory (optional): binary sensor type ExSens	• 24 V DC supply • Inverse-polarity protection • Input: passive potential free binary sensor • Output: potential free contact in the safe area • LED operation indication • Applicable up to SIL 2 • Dimensions (W" H" D) 17,6" 99" 114,5mm • Rail mounting according DIN • Installation in safe area

EXL-IR-9270-11-16-14sC2304 SV switching module

Type	Description/Technical data	Installation module	Installation sensor*
EXL-IR-9270-..	1 module (rail mounting) for 1 passive binary sensor series ExSens	safe area	zone 0, 1, 2, 20, 21, 22
Optional:			
N1 supply unit	Input 120...240 VAC, output 24 VDC, max. 0,5 A, max. 4 pcs. EXL-IR.. connectable. N1 supply unit is required only in case of 120...240 VAC supply!		

*in acc. with certification of sensor!

ExSens Passive, Switching Sensors for Zone 1, 2, 22

Explosionproof		Features ExSens	
ExSens Zone 1, 2, 22 Gas + Dust certified according to ATEX Manufacturer certificate	passive, switching	Description ExSens switching sensors for temperature, humidity or pressure measurement in hazardous locations with manufacturer certification in acc. with ATEX. These sensors are passive and potential free. Delivery: 1 Sensor Ordering example for 1 frost protection thermostat Type to purchase: 1 " TBK-FR-2G	Basics - Sensors for installation in hazardous locations, connected to a switching module type ExBin-A-., RedBin-A-.. or EXL-IR-9270-.. - The module changes the passive binary signal into a contact in safe area - Standard sensor design with integrated scale and adjustment - Sensor is installed in the hazardous location, module in the safe area
			

Sensors, connectable to switching modules type ExBin-A-., RedBin-A-., EXL-IR-9270-..

Type	Function	Range	Sensor	Information	Connectable to module type	Sensor in zone
TBR -2G	Room thermostat	0...+40/+60 °C, 1K/1.5K/2K	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
TBR -2G3D	Room thermostat (IP65)	!30...+35 °C/0...+60 °C, 2-20 K	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2, 22
TBR-2 -2G	Room thermostat 2 stage	0...+40 °C, 1 K	2 " Contact, 2-pos		2 " ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
TBR-AN-2G	Room temperature direct contact	0...+60 °C, 5 ± 1 K (fix)	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
TBK -2G	Duct thermostat (IP65)	0...+90 °C/+50 °C...+140 °C, 3K/1K	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
TBT -2G	Sensor thermostat (IP65)	0...+120 °C/+50 °C...+140 °C, 3K/5K	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
TBT-VA -2G	Sensor thermostat with VA sleeve	0...+120 °C/+50 °C...+140 °C, 3K/5K	Contact, 2-pos	V4A	ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
TBK-FR -2G	Frost protection thermostat (IP65)	!10...+15 °C	Contact, 2-pos	capillary 1.8/3/6 m	ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
FBR -2G	Room hygostat	35...100 %rH, ~ 4 %rH	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
FBK -2G	Duct hygostat	35...100 %rH, ~ 4 %rH	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
DBK -2G	Differential pressure	20-300, 50-500, 100-1.000 Pa	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
DBK -2G3D	Differential pressure (IP65)	40-125, 100-400, 350-1.400, 1000-5000 Pa	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2, 22
LGW-2G-...-SIL	Differential pressure	0,04-0,3/0,1-1/0,25-5/3-15 kPa	Contact, single	SIL	EXL-IR-..	1, 2
WFBK -2G	Air paddle	2...8 m/s, paddle V2A	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2
SWBT -2G	liquid flow switch	!20...+60 °C	Contact, 2-pos		ExBin-A-., RedBin-A-., EXL-IR-..	1, 2

Accessories

Type	Description/Technical data
Installation-Kit-1	for frost protection sensor type TBK-FR-2G, PG entries for capillary, 6 brackets, support bracket
Installation-Kit-2-DBK	includes 2 meter pressure hose (inner diameter Ø6 mm) 2 plastic fittings

..VA/..CT Special Options for Sensors – Overview


Overview of special options of Schischek sensors for use under extreme weather conditions

Application area:

Usage in hazardous locations under extreme weather conditions and/or for offshore/onshore applications.

Advantages:

- Resistant against corrosive and/or maritime atmosphere
- Usage under extreme weather conditions
- Approved for offshore/onshore applications
- Robust and thereby extended period of application time of sensors



..Cos/..Bin/..Reg Special Options for Sensors

Explosionproof	Features ..Cos/..Bin/..Reg-...-VA/OVA/CT/OCT		
Cos/Bin/Reg-...-VA/..CT available for all sensors In accordance with type for use in Ex area or safe area	Special options	Description	Basics
		VA version with housing material in stainless steel similar AISI 316, some parts nickel plated. OVA version also with stainless steel housing but suitable especially for offshore applications. CT version with aluminium housing and offshore/marine coating, resistant against corrosive and maritime atmosphere, some parts nickel plated. OCT version with painted housing like CT, but suitable especially for offshore applications. Delivery: 1 sensor with special option Ordering example: ExCos-P-250-CT	VA: • Housing material in stainless steel similar AISI 316, some parts nickel plated, resistant against corrosive/maritime atmosphere, screws in stainless steel OVA: • Basics like VA, but offered as offshore version with additionally tubes for clamping ring Ø6 mm in stainless steel CT: • offshore/marine coated aluminium housing, resistant against corrosive/maritime atmosphere • Cable glands brass nickel plated, screws in stainless steel OCT: • Basics like CT, but offered as offshore version with M20 cable glands and additionally with tubes for clamping ring Ø6 mm in stainless steel For general basics see description of Cos/Bin/Reg.

..Cos/..Bin/..Reg-.. options

Type	Description/Technical data
Cos/Bin/Reg-...-VA	Housing material in stainless steel similar AISI 316, some parts nickel plated, screws in stainless steel (surcharge)
Cos-P/Bin-P/Reg-V-..OVA	Offshore version with seawater resistant stainless steel housing. M20 cable glands Ni-plated, pressure connection tubes and screws in stainless steel (surcharge)
Cos/Bin/Reg-...-CT	Offshore/marine coated aluminium housing, resistant against corrosive and/or maritime atmosphere. Cable glands Ni-plated, screws in stainless steel (surcharge)
Cos-P/Bin-P/Reg-V-..OCT	Offshore version with seawater resistant offshore/marine coated Al-housing. M20 cable glands Ni-plated, pressure connection tubes and screws in stainless steel (surcharge)
Kit-S8- CBR	Cable glands 2 " M16 " 1,5 mm Ex-e (for cables Ø5-10 mm) in brass nickel plated for replace the plastic cable glands of ..Cos/..Bin/..Reg sensors
Kit-Offs-GL-CBR	Cable glands 2 " M20 " 1,5 mm Ex-d in brass nickel plated for armoured cable suitable for ..Cos/..Bin/..Reg sensors
Kit-PTC- CBR	Pressure tube connection in stainless steel 316 L for 6 mm clamp fittings

ExPolar Heating System – Overview


Overview of new heating system for use with Schischek sensors down to ! 40 °C

Application area:

Usage in hazardous locations for temperatures down to ! 40 °C.

Advantages:

- Especially for usage under high sub-zero temperatures (down to ! 40 °C)
- Used directly in hazardous locations
- Adaptable on all our sensors



ExPolar/InPolar Heating System for ..Cos../Bin../Reg...Sensors

Explosionproof	Industrial	Features ..Polar...-CBR	
ExPolar...-CBR Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx, EAC, CCC	InPolar...-CBR NOT explosionproof and only for use in safe area IP66	Description Controlled heating system for use in sub-zero regions down to ! 40 °C. Adaptable on our sensors ..Cos..., ..Bin... or ..Reg... Delivery: 1 heating system (adaptable) Ordering example: ExPolar-240-CBR	Basics • 24/48 VAC/DC, 120/240 VAC • 60 W • ! 40 °C... +60 °C • ExPolar for zone 1, 2, 21, 22 • InPolar for safe area

ExPolar...-CBR/InPolar...-CBR

Type	Adaptable on	Operation temperature	Supply	Power*	Installation area
ExPolar...-CBR	ExCos../ExBin../ExReg..	!40 °Cupto +60 °C	24 VAC/DC 48 VAC/DC 120 VAC 240 VAC	60 W	zone 1, 2, 21, 22
InPolar...-CBR	InCos../InBin../InReg..	!40 °Cupto +60 °C	24 VAC/DC 48 VAC/DC 120 VAC 240 VAC	60 W	safe area

↑ Supply voltage

*Nominal value

Not suitable for VA versions!

Special option

Type	Description/Technical data
...Polar...-CT	Housing offshore/marine coated, resistant against corrosive/maritime atmosphere, some parts nickel plated (surcharge)

ExArctic/InArctic Heating System for ..Cos../Bin../Reg...Sensors

Explosionproof	Industrial	Features ..Arctic...	
ExArctic-CBR Hazardous Location	InArctic-CBR Safe Area	Description Controlled heating system with protective housing for use down to ! 60 °C. Suitable for our sensors ..Cos..., ..Bin... or ..Reg... Delivery: 1 heating system 1 protective housing 1 mounting material set	Basics • ! 60 °C • ExArctic for hazardous locations • InArctic for safe area • details and prices on request • subject to change

ExMag Electric Door Holder Magnets According to ATEX for Zone 1, 2, 21, 22

Explosionproof		Features ExMag (EXM)	
ExMag	Magnet	Description	Basics
Zone 1, 2, 21, 22 Gas + Dust certified according to ATEX, IECEx		ExMag door holder magnets are electric magnets to keep doors open or closed as long as supply voltage is available. Delivery: 1 magnet Ordering example: 650 N magnet + anchor + Ex-terminal box Type to purchase: 1 " EXM-650+1 GH6 + 1 " EXC-K4/S	• Electric magnets, silicone free • Force in acc. with type • 24 VDC power supply • 1 m cable, silicone and halogen free • Ex-e terminal box is required for electrical connection • The max. AC-ripple must not exceed 20%


Ex-m ExMag Magnets

Type	Force	Supply	Function	Current	Installation in
EXM- 650	650 N	24 VDC	Magnet	45 mA	Zone 1, 2, 21, 22
EXM-1300	1.300 N	24 VDC	Magnet	65 mA	Zone 1, 2, 21, 22
EXM-2000	2.000 N	24 VDC	Magnet	160 mA	Zone 1, 2, 21, 22

Accessories

Type	Description/Technical data
GH-6	Anchor for EXM-650
GH-13/20	Anchor for EXM-1300 and EXM-2000
ExBox-3P	Ex-e terminal box, IP66
EXC-K4/S	Ex-e terminal box, IP66, with integrated fuse
EXC-T1	Ex-d push button
N1 supply unit	Input 120...240 VAC, output 24 VDC, max. 0,5 A

ExComp Different Ex-components

Explosionproof		Features ExComp (EXC...)	
ExComp	Components	Description	Basics
Zone 1, 2, 21, 22 (in acc. to type) Gas + Dust certified according to ATEX		Different explosionproof products like switches, safety temperaturesensors, Delivery: 1 component Ordering example: Switch 20A, 3 pole Type to purchase: 1 " EXC-RS20/3	• No specific information • Data in acc. with every single product/type

ExComp components

Type	Application	Explosionproof	Technical data
EXC-S 10/3...	Switch	II 2G EExed II CT6	10 A - 240/400 V - 2,5/4,6 KW- 3 pole
EXC-S 20/3...	Switch	II 2G EExed II CT6	20 A - 240/400 V - 4,5/9,0 KW- 3 pole
EXC-S 25/6...	Switch	II 2G EExed II CT6	20 A - 240/400 V - 4,5/9,0 KW- 6 pole
EXC-S 40/3...	Switch	II 2G EExed II CT6	40 A - 240/400 V - 11/20 KW- 3 pole
EXC-S 40/6...	Switch	II 2G EExed II CT6	40 A - 240/400 V - 11/20 KW- 6 pole
EXC-DS1/A	Safety temperature sensor	II 2GEx db II CT6 Gb, II 2DEx tb III CT80 °C Db	Duct mounting, potential free contact, switching at 70°C...160°C (10°C steps)

Product Codes/Definitions

Description ..Max quarter-turn actuators

Ex	Max	5.10	SF
Ex is for use in zone 1, 2, 21, 22	Max is a rotary (quarter-turn) actuator for dampers or rotary valves, such as ball or butterfly valves	The numbers show the torque in Nm Two numbers mean that the torque is selectable on site (e.g. 5 or 10 Nm)	S = integrated auxiliary switches, switching at 5° and 85° F = spring-return (German word for spring is "Feder") Y = modulating actuator 0...10VDC or 4...20 mA and feedback signal BF = fire damper actuator, intrinsically safe input for direct ExPro-TT connection (fire trigger) F1/F3 = actuator with fast spring-return (number after letter F shows closing time in seconds, e.g. in ~ 1 or 3 seconds) C = actuator for direct communication with Ex/In Reg controller
Red is for use in zone 2, 22			
In is for use in nonclassified industrial areas			



Description ..Run valve actuators

Red	Run	5.10	Y
Ex is for use in zone 1, 2, 21, 22	Run is a linear actuator for globe style control valves with a stroke between 5 and 60 mm	The numbers show the force in N Two numbers mean that the force is selectable on site (e.g. 500 or 1000 N)	Y = modulating actuator 0...10VDC or 4...20 mA and feedback signal U = floating control on/off, 3 pos. actuator with 0...10VDC or 4...20 mA feedback signal
Red is for use in zone 2, 22			
In is for use in nonclassified industrial areas			



Description ..Cos analog transmitter

In	Cos	P	2500
Ex is for use in zone 1, 2, 21, 22	Cos analog transmitter with output 0...10V or 4...20 mA	P = differential pressure sensor D = module for temperature/humidity for connection of ExPro-C..sensors	The numbers show the measuring range of the differential pressure sensor in $\pm$ Pa
Red is for use in zone 2, 22			
In is for use in nonclassified industrial areas			



Product Codes/Definitions

Description ..Bin binary sensors

Ex Bin - P - 500 - 2

The number stands for a 2-stage adjustable switch-point in measurement range
Without number the sensor comes with 1-stage, adjustable switch-point in measurement range

The number shows the max. adjustment range of the differential pressure switch in Pa

P = differential pressure switch
D = thermostat/hygrostat module for connection of ExPro-B..sensors
FR = frost protection thermostat
A1 = switching module for connection of one passive switch
A2 = switching module for connection of two passive switches

Bin: switching measuring module with output as a potential free contact (1 opener or 1 closer)

Ex is for use in zone 1, 2, 21, 22

Red is for use in zone 2, 22

In is for use in nonclassified industrial areas



Description ..Pro-.. sensors for ..Cos-D or ..Bin-D modules

Ex Pro - CTF - 200

The number shows the length of the sensor in mm

T = temperature sensor
F = humidity sensor
TF = combined sensor temperature/humidity
C = sensor for connection to Ex/Red/InCos-D
B = sensor for connection to Ex/Red/InBin-D

Pro-.. sensor for connection

Ex is for use in zone 1, 2, 21, 22

In is for use in nonclassified industrial areas



Description ..Reg controller

Ex Reg - V - 300 - A

A = Type with analog signals for external communication

The number shows the control range of the controller in Pa (V-type only)

V = volume flow control/pressure control


Reg controller

Ex is for use in zone 1, 2, 21, 22


In is for use in nonclassified industrial areas



Installation zones



Installation FM/CSADiv. classes



- ① Explosionproof actuator (ExMax/RedMax, ExRun/RedRun)
- ② Elbow device ...
- ③ Connecting device ...
- ④ Conduit box ...

- ⑤ Connecting device, max. length 0,46 m (18")
- ⑥ Seal fitting for horizontal or vertical conduits ...
- ⑦ Connecting device reaches into the safe area ...

* Variants for North America on request!

Quarter-turn actuators

..Max
Quarter-turn
actuator



Valve linkage
example



Valve
example



Linear motion actuators

..Run
Linear actuator



Valve linkage
example




Valve
example



Schischek valve linkages

Option 1

You make the linkage yourself or source it somewhere else. In that case we would be happy to provide you with all the actuator dimensions necessary to do so. We can even give you STEP files you can import directly into your CAD system.




Option 2

We design and deliver the linkage.

We can quote you a price for a linkage for any typical valve mounting pattern and stem (for example ISO 5211) without knowing the exact valve dimensions.

When you order the linkage however, we need the dimensions of the top plate/mounting pattern as well as the stem shape and dimensions to design the linkage. The cut sheet for your valve will typically have that information. Simply send us the cut sheet and we will do the rest.



ATEX • IECEx • IP66 • INMETRO • KOSHA



ATEX is a commonly used synonym for the ATEX directives of the European Union. The name is derived from the French term "ATmosphère EXplosible".

The directive encompasses explosion protection directives 2014/34/EU for equipment and 1999/92/EG for work areas. ATEX directives are devised by the Director General of the EU commission Enterprise and Industry in cooperation with the member states, standardization organizations (CEN, CENELEC) and so called "Notified Bodies" such as BAM, PTB, or TÜV to name examples from Germany.



IECEx is an internationally used process to certify electrical equipment used in hazardous locations. The code defines a system to classify locations with potentially explosive atmospheres caused by gases, dusts, or fibers for example.

The main goal of the International Electrotechnical Commission IEC with the IECEx regulation is to reach global harmonization of codes governing use of electrical apparatus in hazardous locations. IEC promotes mutual acceptance of evaluations and reports among the testing labs and certifying bodies.



IP66 stands for Ingress Protection and denotes the protection of the device against environmental factors, dust and rain for example, as well as protection of living beings against dangers of touching high voltage circuits for example. The first digit categorizes ingress of solid objects, the second ingress of water:

- IP6X = dust proof
- IPX6 = water jet proof (with specifies water pressure etc.)



INMETRO (National Institute of Metrology, Quality and Technology) is Brazil's government body responsible for the implementation of measurement, safety and quality standards for electrical and electronic products. It guides the activities of accreditation, inspection, testing and certification bodies in the country.



KOSHA (Korea Occupational Safety and Health Agency) aims to contribute to the national economy by maintaining and improving the safety and health conditions at work through the efficient implementation of projects such as research and development, promotion of industrial accident prevention technologies, provision of technical assistance and training on occupational safety and health, inspection on dangerous facilities and equipment.

Certification with Highest Protection Classes

CSA • UL • EAC • JPEX • CCC



CSA is a global provider of testing and certification services.
CSA is also on the OSHA list of nationally recognized testing laboratories, NRTL.



UL is an independent organization that tests and certifies products with regards to safety. UL tests and evaluates compliance of products, components, materials, and systems against specific requirements. As a result, the UL mark can be carried as long as the standards are complied with. UL is one of the OSHA endorsed testing labs. OSHA is the Occupational Safety and Health Administration and maintains a list of labs called NRTL, short for nationally recognized testing laboratories.




In the context of the Eurasian Customs Union, new technical rules were continuously introduced since June 12, 2012 in order to create a common economic area. This also affects equipment intended for use in potentially explosive atmospheres.

As part of this change, the GOST-RExplosion protection certificate was replaced by the new technical regulation TR CU 012/2011 "On the safety of equipment for use in potentially explosive atmospheres". Instead of the previously required GOST-RExp certificate, it is now necessary to obtain a EAC certification. Likewise, the RTN approval process has been replaced by the TR CU regulations.



Electrical equipment to be used or installed in a hazardous location in Japan must have a valid certificate under JPEX (JPEX certification). Equipment will be issued certificates as a result of Japanese Ex conformity assessment procedures.



The China Compulsory Certification (CCC) is a mandatory safety and quality mark required for many products in the Chinese market, including products involved in industrial automation. Introduced in 2002 and overseen by the CNCA, it ensures products meet safety and quality standards before they can be imported, sold, or used in China.

CCC certification is required when products fall under categories related to electrical safety or hazardous location equipment. In China, products used in industrial automation, especially those with electrical components or explosion-proof features, must comply with CCC regulations to ensure they meet national safety and quality standards.

Regulations for explosion protection

ATEX

Since July 01, 2003 the rules of explosion protection in the EU are set out by directive 94/9/EC (as of April 20, 2016: 2014/34/EU) concerning equipment and protective systems for use in potentially explosive atmospheres. The aim was to replace national provisions in favour of uniform EU-wide rules and regulations to establish uniform safety standards and to eliminate barriers to trade. In 1996, directive 94/9/EC (as of April 20, 2016: 2014/34/EU) was transposed into German law by the German Equipment Safety Act (recast: Product Safety Act) and the Act on Explosion Protection, in short ExVO (11th GPSGV). While directive 94/9/EC (as of April 20, 2016: 2014/34/EU) defines construction requirements, i.e. it is of particular interest to manufacturers of explosion-proof equipment, operators of installations have to observe directive 1999/92/EC for the safety of workers endangered by explosive atmospheres. In Germany, this directive is transposed into German law by the Industrial Safety and Health Act (BetrSichV).

On April 20, 2016, the ATEX directive 94/9/EC will be replaced by the new directive 2014/34/EU. Many changes in the new directive are not relevant for manufacturers of explosion-proof equipment. Most of the essential content remains the same, for example, Annex I "Criteria determining the classification of equipment-groups into categories" and the essential health and safety requirements (EHSR; Annex II) of the directive do not change. Important for both manufacturers as well as operators and plant manufacturers is that EC-type examination certificates issued in accordance with directive 94/9/EC are still valid. A recertification according to directive 2014/34/EU is therefore not required.

ExVO

Directive on the distribution of equipment and protection systems for potentially explosive areas – explosion protection ordinance 11.GSGV.

Ordinance on Industrial Safety and Health Ordinance concerning the protection of safety and health in the provision of work equipment and its use at work, concerning safety when operating installations subject to monitoring and concerning the organization of industrial safety and health at work.

Certificates

Corresponding approvals and certificates are required for electrical explosion protected equipment. Testing must be carried out by an official testing agency (Notified Body, for example the PTB, Physikalisch-Technische Bundesanstalt in Braunschweig/Federal German Physical and Technical Institute in Braunschweig). ATEX approvals are also accepted in many countries and states outside Europe.

The type plate and its components

Responsibilities


The responsibility for compliance with all regulations and directives, from production and planning to installation, operation and maintenance, has greatly increased.

Each individual must be clear on the fact that he accepts personal responsibility as part of an overall project:

- building owners
- end-users
- architects
- consulting engineers/control companies
- inspection authorities
- contractors/installers
- manufacturers
- product suppliers
- maintenance engineers

Example, for the labelling of a quarter-turn actuator

Manufacturer's name, manufacturer's address, designation of type, electrical data (V, A, W, Hz) ambient temperature if different from !20 to +40°C, unit serial number, in addition to the classification of Ex protection.



Correct installation

For the installation of electrical systems in areas with explosive atmospheres of group II, standards IEC 60 079-14 (EN 60079-14) or VDE 0165 apply. In Germany however solely the Technical Rules for Occupational Safety grant the presumption of conformity with the Industrial Safety and Health Act (BetrSichV).

Electric circuits of protection types d, e, q, o, m, p

Installation in the control panel is identical to "standard" installation, however the procedures for connecting Ex equipment must be followed. This relates, for example to voltage, current, fuses and motor protection equipment, etc. The requirements for specific products need to be taken from their corresponding test certificates, standards and regulations as well as from the user manual. It is only permitted to work on electric circuits within the Ex-area (for example when making connections in an Ex-e terminal box) when the voltage has been switched off. An Ex-e terminal box should only be opened after the voltage has been switched off.

Electric circuits of protection type "i" (intrinsic safety)

For the planning and operation of switchgears and control systems installed in the safe area, but which contain circuits leading into the Ex-area, certain requirements need to be considered. This applies especially to intrinsically safe circuits. Intrinsically safe circuits and non-intrinsically safe circuits need to be separated. Minimum distances (tight string length) between bare connections must be observed, the cables must not produce any inadmissible external inductance or capacitance. The maximum admissible electrical limits of Ex-i equipment must be observed at all times. Intrinsically safe and non-intrinsically safe electrical circuits may not be connected together. Connections between two different intrinsically-safe circuits are permitted on the condition that a calculation shows that intrinsic safety is not compromised.

Intrinsically-safe circuits have to be marked as such. When marking is done by means of colours, "light blue" colour has to be used. This colour is recommended for all intrinsically safe circuits to prevent confusion and/or connection to a non-intrinsically safe circuit. Examples: cables, wiring, cable conduits, terminals, terminal boxes, cable glands ...

A minimum distance of 50 mm between intrinsically safe and non-intrinsically safe circuits has to be maintained, and a minimum distance of 6 mm between two different intrinsically safe circuits. During installation the cables of intrinsically safe and non-intrinsically safe circuits are to be routed separately!

Suggestion on how to design a panel
It is necessary to keep intrinsically safe and non-intrinsically safe equipment separate. It is recommended, in this case, that a sufficient distance be kept, to avoid extra costs in the future.

Large transformers, frequency converters, large relays and other electric equipment that may influence intrinsically safe circuits by inductance or capacitance should be installed at a sufficient distance. As a precaution Ex-i equipment should have a suitable cover to protect it from incorrect handling. The appropriate standards and regulations must be observed.




*from April 20, 2016 replacement of ATEX 94/9/EC directives with directives according to ATEX 2014/34/EU

Explosionproof means: "Protection of Life. Health. Assets."

When does the danger of an explosion occur?
A danger of explosion occurs when a flammable medium (gas, vapour, mist or dust) is present in a dangerous quantity.

When does an explosion occur?
An explosion may occur when the following 3 components are present at the same time:

- Flammable or combustible media
- Oxygen
- Source of ignition



Typical sources of ignition
Very often the cause of an accident is self-ignition, hot surfaces and mechanically generated sparks. But there are also a lot of other sources of ignition, caused by either mechanical and/or electrical equipment:

- Self-ignition
- Extraordinary surface temperatures
- Open flames
- Mechanically generated sparks
- Static electricity
- Lightning strike
- Ultra-sonic
- Chemical sources of ignition
- Electric sparks
- Electric arcs
- Adiabatic compression
- Adiabatic shock waves
- Electric circulating currents

Is your system safe?

We have the following situation NOW or in the FUTURE:

Yes.No (Please check)

- ☐ ☐ Flammable materials are stored.
- ☐ ☐ Flammable materials are used.
- ☐ ☐ Flammable materials are bottled.
- ☐ ☐ Flammable materials are used during the cleaning process.
- ☐ ☐ Flammable materials are used in the production process.
- ☐ ☐ Flammable materials will be produced during the production process.

6 "No": Obviously you do not need explosion protection

at least 1 "YES":

When planning you have to consider rules, regulations and instructions concerning explosion protection

Example: ATEX directives, EN 60079-14

Remarks:

All information, tables, checklists and further documentation are only for your assistance and do not claim to be complete. In no way do they replace official regulations and rules or even laws by the authorities. We want to point out that it is very important to undertake all measures for an exact classification of the Ex-area.

Typical Applications:


- Chemical, pharmaceutical and industrial plants
- Refineries, petrol depots, gas stations
- Paint and solvent shops
- Drying and coating cabinets
- Laboratories in industry and schools
- Water treatment works, power plants
- Compressor stations, gas works
- All kinds of storekeeping and stocks
- All kinds of filling stations
- All kinds of cleaning stations
- Mills, silos, silos for bulk goods
- Offshore and onshore
- Oil and gas pipelines
- Printing works, food industry, ...

Schedule:

- Analyse whether you need explosion protection or not
- Ask experts in order to analyse the risk
- Define zones, areas, categories, explosion groups and temperature classes
- Planning according to all necessary rules and regulations
- Choose the best supplier and the right product
- Keep to the installation rules
- Check the labelling of the equipment
- Make sure that the appliance will be put into operation correctly
- Confirm a final inspection by the responsible authority
- Guarantee regular and correct maintenance according to the regulations
- The correct documentation has to be maintained

From combustion to detonation

Effect and reaction velocity increase significantly from combustion, deflagration, via explosion up to detonation. Explosions are more likely with gaseous media and detonations with dust media.



Introduction

Areas with potentially explosive atmospheres are divided into zones, equipment has to be divided into groups and categories. The marking on the identification plate of certified equipment indicates in which zone the explosion protected equipment can be used.

Division into product groups

Equipment is divided into group I and group II. Group I deals of underground mines and group II deals with all other applications.

Division into zones

Areas with potentially explosive atmospheres are divided into six zones according to the probability of how frequent and for which period of time a potentially explosive atmosphere (p.e.a.) exists.

A distinction is made between combustible gases, mists, vapours and combustible dust. For gases, mists and vapours zones 0, 1 and 2 exist, in which the requirements for the chosen equipment increase from zone 2 to 0. Equipment in zone 0 must be built in a way "that even if a type of protection fails or if two faults occur, that sufficient explosion protection is guaranteed". Therefore for example a passive, potential free sensor, installed in zone 0, and connected to an intrinsically safe electric circuit (II 2 (1) G[Ex ia] IIC), needs its own approval. Zones 20, 21 and 22 are for dust atmospheres, in which the requirements for the chosen equipment increase from zone 22 to 20. Equipment in zone 20 and 21 need special approval.


Division into equipment groups

Equipment groups determine, in which zones the equipment may be installed. Once again there are six categories. Categories 1G, 2G and 3G are classifications for gas explosion protection (G = Gas); thereby 1G equipment is suitable for use in zones 0, 1 and 2, 2G equipment is suitable for use in zones 1 and 2 and 3G equipment is suitable for use in zone 2. Categories 1D, 2D and 3D are classifications for dust explosion protection (D = Dust); thereby 1D equipment is suitable for use in zones 20, 21 and 22, 2D equipment is suitable for use in zones 21 and 22 and 3D equipment is suitable for use in zone 2.

Classification and labelling of hazardous locations


Flammable medium	Hazardous locations Probability of a potential explosive atmosphere occurring	Classification of hazardous locations	Product classification		Equipment protection level (EPL)
			Product Group	Product Category	
Gases Vapours Mists	Continuously, for long periods or frequently	Zone 0	II		
	Likely to occur	Zone 1	II	1G	Ga
	Infrequently and for short periods only	Zone 2	II	2G 3G	Gb Gc
Dusts	Continuously, for long periods or frequently	Zone 20	II		
	Likely to occur	Zone 21	II	1D	Da
	Infrequently and for short periods only	Zone 22	II	2D 3D	Db Dc

Zone 0, 1 and 2



An example of a typical zone distribution would be filling a barrel of petrol in an enclosed area.

Zone 20, 21 and 22



An example of a typical zone distribution would be filling a grain silo in an enclosed area.

Explosion groups, temperature classes

The equipment groups and categories determine, in which zones the equipment may be installed, whereas the explosion groups and temperature classes determine, for which mediums inside the zones, the equipment is suitable. The type of protection used is not a mark of quality but is instead a constructive solution for selecting equipment for explosion protection.


Division into explosion groups

Explosion protected equipment for gases, mists and vapours is divided into three explosion groups (IIA-IIIB-IIC) according to the type of protection being used. The explosion group is a means to measure the ignitability of gases (potentially explosive atmospheres). The equipment requirements increase from IIA to IIC.




Division into temperature classes

Explosion proof equipment, installed within an Ex area, is divided into 6 temperature classes (T1 to T6). The temperature class is not – as it is often wrongly believed – the operating temperature range of the equipment, but the maximum permissible surface temperature of the equipment, in relation to + 40°C ambient temperature on any surface area, which may not be exceeded at any time. The maximum surface temperature must remain below the ignition temperature of the surrounding medium at all times. The equipment design requirements increase from T1 to T6.




Air safety dampers • Air control dampers • Fire/smoke dampers



Air damper control

Our actuators are approved for direct installation and operation in explosive atmospheres, as they are of the highest explosion groups and temperature class and are suitable for all gases, mists, vapours and dust.


During installation please ensure that all cables are securely fixed and connected in such a way that they are protected from mechanical damage. For electrical connection an explosion protected terminal box (type ExBox-...) has to be used.



Automatic air damper control

In this example the control system consists of an actuator and an ExCos-D transmitter with ExPro sensor. The combination can be installed directly in an Ex area. The transmitter converts the sensor signal into an active signal (0...10 VDC or 4...20 mA) for input in a PLC system. The output signal from the controller goes directly to the actuator.

Between sensor and controller an additional Ex-i module and intrinsically safe (IS) circuit wiring are not required. For the actuator and transmitter the maximum permissible surface temperatures have to be taken into account.




Control of fire/smoke dampers

In applications for fire/smoke dampers, the actuator has to reliably return the damper to its safety position via an external switch/contact.

The actuator closes the damper mechanically by means of an internal spring. The closing operation is triggered by a safety thermal trigger of type ExPro-TT-...


Heating • Cooling • Humidification • Diff.pressure control • VAV



Heating/cooling control

In this example the control system consists of an actuator and an ExCos-D transmitter with ExPro sensor. The combination can be installed directly into an Ex area. The transmitter converts the sensor signal into an active signal (0...10 VDC or 4...20 mA) for input in a PLC system. The output signal from the controller goes directly to the actuator.


Between sensor and controller an additional Ex-i module and intrinsically safe (IS) circuit wiring are not required. For the actuator and transmitter the maximum permissible surface temperatures have to be taken into account.



Humidity control

In this example the control system consists of a valve actuator and an ExCos-D transmitter with ExPro sensor. The combination can be installed directly into an Ex area. The transmitter converts the sensor signal into an active signal (0...10 VDC or 4...20 mA) for input in a PLC system. The output signal from the controller goes directly to the actuator.

Between sensor and controller an additional Ex-i module and intrinsically safe (IS) circuit wiring are not required. For the actuator and transmitter the maximum permissible surface temperatures have to be taken into account.




Differential pressure control/VAV

In this example the control system consists of an actuator and a differential pressure ExCos-P transmitter. The combination can be installed directly in an Ex area. The transmitter converts the differential pressure signal into an active signal (0...10 VDC or 4...20 mA) for input in a PLC system. The output signal from the controller goes directly to the actuator.

Between sensor and controller an additional Ex-i module and intrinsically safe (IS) circuit wiring are not required. The controller is located in the safe area and delivers an output signal for example via a frequency converter to control a fan (must be Ex protected) or a modulating damper actuator (also Ex protected) to maintain the required air volume/pressure. The technical specifications can be found in the approval documents.


Thermostats • Humidistats • Pressostats • Filter monitoring



Thermostats

ExBin-D... modules with ExPro-BT... sensor are thermostats for use in potentially explosive atmospheres. No intrinsically-safe electrical circuits and no switching amplifiers need to be installed in the electrical control-panel. The module may be installed directly in an Ex area, depending on demand in zone 1, 2, 21 or 22.


The output contact can be used for follow-up functions (relays, contacts, direct circuit, ...).



Hygrostats

ExBin-D... modules with ExPro-BF... sensor are hygrometers for use in potentially explosive atmospheres. No intrinsically-safe electrical circuits and no switching amplifiers need to be installed in the electrical control-panel. The module may be installed directly in an Ex area, depending on demand in zone 1, 2, 21 or 22.

The output contact can be used for follow-up functions (relays, contacts, direct circuit, ...).




Filter monitoring

ExBin-P... modules are pressostats like Ex-differential pressure switches, e.g. for filter monitoring in potentially explosive atmospheres. No intrinsically-safe electrical circuits and no switching amplifiers need to be installed in the electrical control-panel. The module may be installed directly in an Ex area, depending on demand in zone 1, 2, 21 or 22.

The output contact can be used for follow-up functions (relays, contacts, direct circuit, ...).


Drive (Fan) belt monitoring • Frost protection



Drive (fan) belt monitoring via differential pressure

ExBin-P... modules are pressostats like Ex-differential pressure switches, e.g. for fan belt monitoring in potentially explosive atmospheres. No intrinsically-safe electrical circuits and no switching amplifiers need to be installed in the electrical control-panel. The module may be installed directly in an Ex area, depending on demand in zone 1, 2, 21 or 22. To indicate fan failure switching modules are delivered with integrated time running relay with delay on start up.


The output contact can be used for follow-up functions (relays, contacts, direct circuit, ...).



Frost protection

ExBin-FR... are sensors for frost protection monitoring with a capillary as measuring element for use in potentially explosive atmospheres. No intrinsically-safe electrical circuits and no switching amplifiers need to be installed in the electrical control-panel. The module may be installed directly in an Ex area, depending on demand in zone 1, 2, 21 or 22.

The output contact can be used for follow-up functions (relays, contacts, direct circuit, ...).



Fan belt monitoring via NAMUR sensor

EXL-IR-9270 switching modules in combination with connected NAMUR sensor (inductive proximity switch) are suitable for non-contact V-belt monitoring of fans in hazardous locations.

The switching module is installed in the safe area. Wiring is via an intrinsically safe Ex-i circuit. The proximity switch type NAMUR is installed in the hazardous location, depending on the sensor type and certification in zone 1 or 2.

The input of the switching module is a passive, potential-free, binary signal, the output is a potential-free, switching contact.

Damper Actuation Focused

One air-damper – various actuator solutions!



Electric actuators with
or w/o spring-return





Betec Controls BV
Sleutelbloemstraat 40
NL-7322 AK Apeldoorn

+31 (0)55 20 325 30
info@beteccontrols.nl

Trusted partner for Schischek solutions for over 35 years

PUB113-001-00
Issue 09/25